



Gasoline — Portable — Belt Drive



DC-4004-W5H6G

This series is known as the workhorse of the industrial pressure washer line. It is equipped with a heavy-duty belt drive system and powder coated steel frame.

PUMP

- External bypass system protects from heat build-up
- Factory preset stainless-steel and brass unloader (DC-3504 and DC-4004 models feature Mi-T-M unloader)
- Forged brass manifold (Nickel plated brass on DC-4004 models)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

ENGINE

- Performance-proven OHV engine with low-oil shutdown

FRAME

- Powder coated steel frame and base plate with 1¼-inch tube handles
- Two-piece belt guard
- 13-inch flat-free tires

COMPONENT

- Heavy-duty dual cogged belt drive system

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x ¾-inch non-marking high pressure hose
- 48-inch lance with rubber grip (36-inch on DC-2505 and DC-3004 models)
- Professional-grade insulated trigger gun with safety lock-off

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ETL Certified – US (Honda and Vanguard engine models)



Premium Series

Cold Water – Gasoline – Portable – Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-2505-W4H6G	2500	4.4	389cc Honda GX390 OHV ⁺	General	45.5x28x26in.	290 lb.	216 lb.
DC-3004-W4H6G	3000	3.5	389cc Honda GX390 OHV ⁺	General	45.5x28x26in.	290 lb.	216 lb.
DC-3504-W5H6G	3500	3.8	389cc Honda GX390 OHV ⁺	General	46x28x30in.	290 lb.	216 lb.
DC-3504-W5K6G	3500	3.8	429cc Kohler CH440 OHV	General	46x28x30in.	290 lb.	216 lb.
DC-3504-W5M6G	3500	3.8	420cc Mi-T-M OHV	General	46x28x30in.	290 lb.	216 lb.
DC-4004-W5H6G	4000	3.5	389cc Honda GX390 OHV ⁺	General	46x28x30in.	290 lb.	216 lb.
DC-4004-W5V6G	4000	4.0	480cc Vanguard OHV with electric start – battery not included	General	46x28x30in.	330 lb.	256 lb.

⁺49 state engine. Not for sale in California.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0338	50-foot x 3/8-inch non-marking hose – High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	DC-2505-W4H6G & DC-3004-W4H6G
CX-0054	Roll cage – Designed to protect equipment, comes with a lifting hook, 1 1/4-inch powder coated steel tubing	All Honda, Kohler and Mi-T-M engine models
CX-0055	Roll cage – Designed to protect equipment, comes with a lifting hook, 1 1/4-inch powder coated steel tubing	DC-4004-W5V6G
CX-0113	Electric start – battery not included – For easy starting	All Honda engine models



DC-3504-W5H6G

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.