

Trail Blazer

#1 in North America for High-Pressure Cleaning Equipment **TRB-3500 Trailer System**

Hotsy offers an affordable trailer to provide mobile cleaning anywhere. It's easy - you simply select a hot water pressure washer from a list of available units designed to fit on the trailer and you're ready for on-site cleaning.

For On-The-Go Cleaning

Heavy-duty chassis is made of durable 10 gauge steel; 2-by-4 inch formed channel design covered with powder-coated wrinkle black finish for weather protection

Electric **brakes** with brake-away kit are standard features

Durable **steel hoop** holds the hoses and is hose reel ready. **Optional hose reels** (shown) connect to the chassis quickly; holds up to 150 ft. of high pressure hose; 2nd reel holds 100 ft. garden hose

Standard high-density white polyethylene water tank with 200 gallon capacity

Wand storage and signage location

shown with Hotsy 1080BE pressure washer; pictured with optional rock guard, tool box & hose reel



3-way ball valve allows for the water flow to be diverted from the holding tank to a direct water feed from a hose faucet

200 Gallon water tank features a 7-inch access port plus a 2-inch drain, 1-inch **float valve** and 50-mesh outlet filter

Features 15-inch white spoke wheel assembly

Axle assembly features a leafspring suspension under-carriage rated at 3,500 lbs.; DOT approved **Swivel jack trailer tongue assembly** is made to handle up to 1,000 lbs. and features a 2-inch ball coupler for quick & easy hook up of the trailer; 5/16-inch chains are included for additional safety

39-inch tongue length with **swing-away hinge** (rated to 3,500 lbs) means less storage space is needed

FEATURES

- 200 Gallon Water Tank
- Single axle rated to 3500 pounds
- Swing away hinged tongue, saves storage space
- Electric brakes with brake-away kit
- Pick your hot water pressure washer

Frame features a license plate holder and recessed lights; all electrical wiring is recessed within the frame Includes rear **receiver assessory mount** (not for towing) to accept optional rear utility rack

www.Hotsy.com

TRAIL BLAZER TRB-3500 Mobile Trailer Unit For On-The-Go Cleaning

■ 3500 lb. Rated Single Axle

■ Swing Away Hinged Tongue

200 Gallon Water Tank

■ Hot Water Pressure Washer

Designed for mobile hot water cleaning. Select a pressure washer and add water.

TRB-3500 TRAILER SPECIFICATIONS									
MODEL	Gross Weight	Water tank Capacity	Axle	Wheels	Jack	Jack Capacity	Ball Coupler	Safety Chains	Lighting
TRB-3500	3500 lbs	200 gal	Single 3500 lbs	15" White Spoke Wheels ST205/75D15 Tires	Swivel Wheel w/Caster Foot	1000 lbs	2"	Dual 5/16"	Recessed Lights are DOT approved

Trailer Dimensions 136" L x 66" W x 52" H Gross Vehicle Weight Rating (GVWR) lbs. - 3500 Trailer Weight: 543 lbs.

Shipping Weight: 1043 lbs.* *does not include pressure washer

GAS ENGINE HOT WATER PRESSURE WASHERS COMPATIBLE WITH THE TRB-3500



Model 965B

3.0 GPM at 3000 PSI Honda engine (270 CC's / 9 HP) 12 V DC Burner / Oil-Fired **Belt Drive**



Model 1075BE

3.8 GPM at 3500 PSI Honda engine (389 CC's / 13 HP) Electric Start 12 V DC Burner / Oil-Fired Belt Drive



(Shown with optional stainless steel coil wrap and skid rails)

Model 1080BE

4.6 GPM at 3500 PSI Vanguard engine (479 CC's / 16 HP) **Electric Start** 12 V DC Burner / Oil-Fired Belt Drive



1260SS

1200 Series

10 models available 4.3 to 5.6 GPM 3000 to 4000 PSI Honda or Vanguard Engines **Electric Start** 12 V DC or 120 V AC Burner Oil-Fired **Belt Drive**

TRB-3500 TRAILER OPTIONS

- Hydraulic Brakes (factory installed)
- Hose Reels and Mounting Kits protects and easily stores hoses
- Side Saddle Tool Boxes stores small tools
- Rear Utility Rack ideal for carrying additional equipment or detergent (150 lb. rated)
- Front Rock Guard protects the pressure washer
- Chrome wheel rims

A member of KÄRCHER North America



Optional Hose Reel and Mouting Kit



Optional Rear Utility Rack



Optional Side Saddle Tool Box



Optional Rock Guard (shown with hinged trailer tongue

Distributed by:



Tel: (800) 525-1976 www.Hotsv.com P/N 9 800-424 0

Fax: (888) 880-9631 email: info@Hotsy.com Effective 4/16 Specifications & product descriptions subject to change without notice.











NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at $\pm\,10\%$ and in some cases are tighter within ±5% of listed specifications.