



Antegowheels.com/lawn-and-garden

ATW-003



Features:

The turf tread is designed to maximize traction and stability. The rounded shoulder of the tire will protect the turf when turning. Available in a number of standard commercial sizes with durable construction for extended service life.

Specifications:

PART NUMBER	TIRE SIZE	PLY RATING	OVERALL DIAMETER (m/m/in)	S.W. (m m/in)	TIRE PRESSURE psi	MAX LOAD lbs	RIM SIZE inch
T0302114005	11x4.00-5	2	276/10.9	102/4.0	22	210	3.00
T0304114005	11x4.00-5	4	276/10.9	102/4.0	46	325	3.00
T0302135006	13x5.00-6	2	311/12.2	128/5.0	20	295	4.50
T0304135006	13x5.00-6	4	316/12.4	128/5.0	40	440	4.50
T0304136506	13x6.50-6	4	333/13.1	160/6.3	28	460	5.00
T0302156006	15x6.00-6	2	363/14.3	155/6.1	14	365	4.50
T0304156006	15x6.00-6	4	380/15.0	160/6.3	30	570	4.50
T0304166508	16x6.50-8	4	400/15.7	165/6.5	28	620	5.375
T0306166508	16x6.50-8	6	412/16.2	167/6.6	42	785	5.375
T0304188508	18x8.50-8	4	449/17.7	210/8.3	22	815	7.00
T03041885010	18x8.50-10	4	478/18.8	206/8.1	22	795	7.00
T030418105010	18x10.50-10	4	485/19.1	250/9.8	20	990	8.50
T03042010008	20x10.00-8	4	500/19.7	236/9.3	22	1190	7.00
T030420100010	20x10.00-10	4	505/19.9	243/9.6	22	1160	8.00
T0304208008	20x8.00-8	4	507/20.0	207/8.1	22	950	6.50
T03042080010	20x8.00-10	4	505/19.9	216/8.5	24	895	7.00
T03042385012	23x8.50-12	4	579/22.8	206/8.1	22	1120	7.00
T030423105012	23x10.50-12	4	585/23.0	250/9.8	20	1340	8.50
T030424120012	24x12.00-12	4	606/23.9	295/11.6	20	1710	10.50
T030624120012	24x12.00-12	6	615/24.2	295/11.6	32	2260	10.50
T030824120012	24x12.00-12	8	610/24.0	293/11.5	50	2910	10.50
T030426120012	26x12.00-12	4	650/25.6	312/12.3	20	1780	10.50
T030626120012	26x12.00-12	6	655/25.4	310/12.2	35	2450	10.50
T030826120012	26x12.00-12	8	655/25.4	310/12.2	50	3020	10.50
T030427120015	27x12.00-15	4	680/26.8	292/11.5	30	1962	10.00