



**NOTES**

1. INLET CAN ACCOMMODATE UP TO 150MM DISCHARGE HOSE. (LARGER SIZES AVAILABLE UPON REQUEST)
2. CUSTOM SIZES AVAILABLE TO CONFORM TO ANY FOOT PRINT.
3. SEDIMENT BAD IS FOLDED AND PACKED FOR EASY STORAGE (TIE STRAP INCLUDED)
4. **WARNING:** ANCHOR HANDLES ARE NOT INTENDED FOR LIFTING.
5. DEVRON IS NOT RESPONSIBLE FOR AND DAMAGES OF INJURIES RELATED TO SEDIMENT BAG BEING USED FOR ANY PURPOSE OTHER THAN ITS INTENDED USE.

**DN160 (TYPE2) NON-WOVEN GEOTEXTILE**

PROPERTY	TEST METHOD	ENGLISH (MARV <sup>2</sup> )	METRIC (MARV <sup>2</sup> )
Grab Tensile Strength	ASTM D 4632	160 lbs.	0.711 kN
Grab Elongation	ASTM D 4632	50%	50%
Trapezoid Tear Strength	ASTM D 4533	60 lbs.	0.267 kN
CBR Puncture Resistance	ASTM D 6241	410 lbs	1.823 kN
Permittivity <sup>+</sup>	ASTM D 4491	1.5 sec <sup>-1</sup>	1.5 sec <sup>-1</sup>
Water Flow <sup>+</sup>	ASTM D 4491	110 gpm/ft <sup>2</sup>	4480 l/min/m <sup>2</sup>
Apparent Opening Size (AOS) <sup>3&amp;4</sup>	ASTM D 4751	70 Std. U.S. Sieve	0.212 mm
UV Resistance	ASTM D 4355	70%/500 hrs.	70%/500 hrs.

SCHEMATIC FOR SEDIMENT BAG  
DEVRON SALES  
GENERAL SPECIFICATIONS AND LAYOUT DETAIL



PROJECT No.	-
DATE:	2/08/22
SCALE:	N.T.S.
DWG No.	1 OF 1