



Don't let its size fool you; the small but mighty Mystic Mini packs an astonishing output complemented by our new advanced heating technology, all at a fractional size of the original Mystic. With multiple fluid densities and integrated presets, there is nothing the Mystic Mini can't handle. Set it down, start it up, and get to work - anytime, anywhere.

TECHNICAL SPECIFICATIONS

Rated Voltage: 120vac Frequency: 50/60hz

Power Consumption: 900W/7.5 amps

Breaker: 10A 250V









- ▶ 2x Integrated Presets "Light Haze" & "Haze for Daze"
- ► Tank Capacity: 2.5L
- ► Control: DMX, RDM, Manually
- ► Low Fluid Sensor
- ► 50 Second Warm-Up
- ► Automatic Self Cleaning
- ► Neutrik Powercon True1
- ► 5-pin Neutrik DMX (3ch. Power, Haze, Fan)
- ► Integrated Timer
- ► No CO2 Required
- ► Directional Output
- ► Haze Color: Pure White



Compatible Master FX Fluids:

Nebulous (thin density) | Obscure (thick density)

FLUID CONSUPTION RATES (GPH = GALLONS PER HOUR)

Nebulous

100% Output = 2.5L in 5.2 hrs (0.13GPH) 75% Output = 2.5L in 5.9hrs (0.11GPH) 50% Output= 2.5L in 8.3hrs (0.08GPH)

Obscure

- ETL Listed: Certified to CSA STD C22.2# 104

- Mounting point: Hanging bracket replaces handle

100% Output = 2.5L in 3.5 Hrs (0.19 GPH) 75% Output = 2.5L in 4.6 hrs (0.14GPH) 50% Output = 2.5L in 6.9 hrs (0.095 GPH) 25% Output = 2.5L in 13.9hrs (0.047 GPH) 25% Output = 2.5L in 13.9 hrs (0.047 GPH)


OVERVIEW + DIMENSIONS



weight: 21lbs

weight: 36lbs





DOWNLOAD CAD

MYSTIC MINI TOUR PACKAGE





OPTIONAL ACCESSORIES

- Universal Mounting Brackets

- Safety cable attachment point

- Quick Dissconnect Fluid Fittings - 5ft PowerCon True1 (16AWG)

- Road Case

RIGGING

APPROVALS

INCLUDED ITEMS - 2.5L Fluid Container