

## 1300 052 052uvguard.com

-

0

# **CWP-Series**<sup>™</sup>

**Residential** 

### Complete water purification solution in one compact, weather-resistant unit.

UV Guard's CWP-Series purifies water to allow it to be safely consumed or used throughout your home.

The unit delivers complete water treatment in 3 stages – filtration, adsorption and UV disinfection – to remove sediment, bacteria and other pathogens while improving taste, clarity and odour.

### Applications

U uvguard





Kainw



## 1300 052 052uvguard.com

### **Key Features**

- Destroys 99.99% of pathogens including E. Coli, Cryptosporidium and Giardia making it safe for drinking
- Removes sediment and improves taste, colour and odour of rainwater, bore water and town water
- Corrosion-resistant stainless-steel bracket and lockable cover
- **Premium twin filter housings** with pleated washable filter and silver impregnated carbon block filter
- Australian WaterMark-certified 316L stainless steel UV reactor with lamp operation view port and digital controller
- Pre-assembled for quick 'plug & play' installation.





С

Sediment Filtration Removes common water impurities such as silt, dirt and rust.


First Stage

### 2 Second Stage Adsorption

Silver-impregnated antibacterial carbon block filter improves taste, odour and clarity whilst preventing bacteria from establishing.

#### 3 Third Stage UV Disinfection

Chemical-free process that destroys bacteria and other harmful pathogens in the water. No pathogen is known to be immune to UV Disinfection.



#### **Models & Specifications**

Model	Dimensions			UV Dose Flow Rates*				
	A	В	С	16mJ/cm <sup>2</sup>		30mJ/cm <sup>2</sup>		40mJ/cm <sup>2</sup>
CWP30	60	66	22	78 lpm		42 lpm		31 lpm
CWP55	60	74	22	142 lpm		77 lpm		56 lpm
Model	Inlet	Outlet	Sedim Filte		Adsorption Filter		UV Lamp	Maximum Pressure
CWP30	1" Female	1" Male	20 mig				30W	700 kDm
CWP55	BSP (25mm)	BSP (25mm)		pleated washable		antibacterial carbon		700 kPa

WaterMark