

# AQUA SAFE

Water Filtration Systems

## Commercial Water Filter Systems



### Food and Beverage

### Application

For sediment, chlorine, chloramine, THM's, organics, tannins, bad taste, odour reduction and scale protection for food and beverage water supply applications including coffee and tea brewers.

Purified water preserves brand quality, extends equipment longevity, reduces maintenance costs and best of all, keeps your customers coming back for more!



## QC Coffee Pro

<b>System Part:</b>	QC Coffee Pro
<b>Replacement Cartridge:</b>	QC350-ICP
<b>Rated Capacity</b>	
Chlorine:	39,000 litres
Chloramine:	24,000 litres
<b>Service Flow Rate:</b>	8.5 litres/minute
<b>Micron Rating:</b>	5.0
<b>Min/Max</b>	
Pressure:	200–865 kPa
Temperature:	4°C - 38°C
<b>Inlet/Outlet Size:</b>	10 mm (3/8")
<b>Shipping Weight:</b>	1.0 kg
<b>Dimensions (H/W/D):</b>	390/90/125mm
<b>Warranty:</b>	5 years

### Features and Benefits

- The pre-filter is built in, avoiding the need for a separate sediment filter, protecting the carbon.
- Ultra high porosity carbon with micro structure technology engineered to provide superior results at four times higher flow rates and capacities than traditional carbon filters.
- Quick change cartridges provide sanitary changeouts reducing contamination while making it quick and easy.
- Cartridges are made from recyclable materials.
- Filter replacement required only once a year.
- Reduces equipment maintenance due to minimised sediment build-up and chlorine/chloramine corrosion.
- Minimal space required for installation and servicing.
- Improves the taste of beverages.

### Technical Notes and Specifications

- NSF Certified Cartridge.
- Cartridge body and system is manufactured from high impact resistant polypropylene and Nylon materials approved by NSF and the FDA.
- The filter contains scale inhibitors to protect equipment from scale buildup and damage.
- The service flow is maintained for the rated capacity of the filter.
- Pressure gauges, shut off valves and various inlet and outlet fittings can be assembled prior to shipment or can be configured upon request.

*Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.*