

Yamaha After-Market Ballast Bag Installation

Helpful Tips . . .

Use an air pump to inflate the ballast bag and then secure the bag with ropes before filling bag with water.

As you fill the bag with water open the air release value located at the top. You will have a seamless and fast fill time and will not need to adjust the bag at all!

WARNING: Black grab handles/Gray Staple Anchors are NOT meant to hold the bag's weight. They are only guides for the ropes or straps to not slide while securing & filling the bag. If the bag is filled 100% it will not move on the swim platform while surfing. Secured ropes or straps will have pressure against the bag and should not have pressure on the handles. **DO NOT UNDERFILL THE BAG.** This will cause the water inside to move around while surfing, making the bag unstable on the swim platform.

NOT FOLLOWING INSTALLATION INSTRUCTIONS / IMPROPER INSTALLATION CAN CAUSE DAMAGE TO THE SAC. DAMAGE DUE TO IMPROPER / INCORRECT INSTALLATION WILL NOT BE COVERED BY WARRANTY



Installation Video

<https://youtu.be/iFtT4nOV6E>

GOOD INSTALLATION



IMPROPER INSTALL



Above images are examples of bad installations and not covered under warranty. Don't tie handles together. The rope must go through all 4 tie down cleats.



FATSAC™

WWW.FATSAC.COM
@FATSACWAKE
@FLYHIGHWAKE