



Jiangsu Xinri E-vehicle Co.,Ltd.

Email: info@sunraev.com

No.501 Xishan Road, Anzhen , Xishan District ,Wuxi, Jiangsu Province, P.R.China

Tel: 86- 0510-88109820

www.sunraev.com www.mikuev.com

MIKU MAX Operator's Manual

CONTENTS





WARNING!

Read and understand all safety precautions in this manual before operating.

Failure to comply with instructions in this manual could result in personal injury, property damage, and/or voiding of your warranty.





It is your responsibility to know and obey all applicable local, state, and federal laws at all times while operating this electric scooter including but not limited to traffic safety, vehicle registration, emissions, and noise.

01/Safety Guidelines-Definitions

This manual contains important information that you need to know and understand in order to protect YOUR SAFETY and to PREVENT EQUIPMENT PROBLEMS. The following symbols help you recognize this information. Please read the manual and pay attention to these sections.

	DANGER: Damages indicate a certainty or strong possibility of personal injury or death if instructions are not followed.
A	WARNING: Warning indicates a strong possibility of equipment damage or possibility of personal injury if instructions are not followed.
0	CAUTIONS: Cautions indicates a possibility of equipment damage if instructions are not followed.



WARNING: Improper operation or maintenance of this scooter could result in serious injury and property damage. Read and understand safety instructions tips and operating instructions before using this scooter. A blaws obey all apolicable local, state, and federal laws when operating this scooter.

Save These Important Safety Instructions!



Read and understand all of these safety instructions. Be sure to retain them for future use.



02/General Precautions

- Read and follow all instructions in the manual of MIKU products, before attempting to operate this scooter. Don't discard this Operator's Manual, or any other material or documentation included with this scooter.
- Modifying the scooter and/or removing original equipment and/or safety decals could make this scooter unsafe for operation.
- . Replace any safety decals that become unreadable or detached from the scooter. Decals provide critical warning about potential hazards or safety requirements.

Traffic safety



Always follow the entire pre-ride checklist prior to starting or operating the scooter.



Your safety while riding this scooter depends entirely on your ability to exercise proper judgment. You must be of sufficient age, understanding, mental capacity, and physical capability to safely operate this scooter.



Always obtain mature, supervised instruction and sufficient practice this scooter on any public





applicable traffic safety laws while operating this scooter, being sure traffic conditions and slow down if necessary

Traffic safety



Use extreme caution when riding on wet, slippery, rough, or sloped terrain. There is an increased risk property damage.



Use extreme caution when riding on wet, slippery, rough, or sloped terrain. There is an increased risk of loss of control, which can result in injury. death, and/or property damage.





Stop the scooter and shut off the motor immediately if the scooter makes unusur noises or vibrations. Check the spooter for damage. Excessive noise or vibration is a sign

Never operate scooter while under the

of any kind. Such operation is dangerous

to yourself and/or others and may be illegal in your location.

influence of alcohol, drugs or medication





Never use this scooter to perform any type of racing, stunt riding lumps, spin-outs, donuts, or other maneuvers. You could and/or cause property damage.











03/ The manual of smart chip charger

Instruction

0.4

- The charger should be matched with the alternating voltage of local power supply before connecting charger.
- The charger is designed and tested for original battery from manufacturer. Do not use them for the other microstribing batteries.
- The charger is tested and matched with its scooter. If the charger is used on other scooters, it might make different charging effect and/or cause battery damage.
- Please connect charger and scooter before connect to local power supply, while you are going to charge the battery. Please disconnect the charger from local power supply while the battery is fully charged. Don't disconnect charger and scooter while the charger is connected with local power supply for safety reason.

- Do not violently shake the charger. It might cause damage of the charger.
- Keep the charger away from any water, dust or high temperature.
- The charger creates the heat while working. It should be stored in well ventilated place and keep away from any inflammable things.
- Keep it away from children.
- If any wire or shell was broken, Please send it to the professional repairing service. Don' t open or repair it
 vourself. This action will cause danger and lose warranty of the charger.
- The charger is designed and made for electric scooter battery charging use. Don't make it for other use.
- Any incorrect usage which does not follow this instruction will lose guarantee from seller.









Using direction


- While the charger is connected with battery, green light is turned on to indicate the testing status of charging.
- While the charger is connected to 110V/220V/250V local AC power supply, the green light turns to red to indicate charging status.
- After 4-6 hours charging, the red light turns to green to indicate the battery charging is finished.
- While the charging is finished, the charger will cut off power from AC power supply automatically.

04/performance

The performance of an electric scooter is different from gasoline engine driven or human powered vehicles. It's very important to understand how the MIKU electric scooter works before riding.







Test condition: New vehicle with new battery, Temperature at 20°C, No wind, All lights (on the scooter) off, loading weight at 75kg, standard pressure.

- Riding habit, Road conditions, environment and temperature might shorten the riding distance of per charge.
- . Tire pressure and loading weight shorten driving distance of per charge.
- The riding distance of per charge might shorter in Winter because of battery's peculiarity.
- . Riding distance of per charge will be shortened by battery lifetime loss.

08

MIKU

DESIGNED BY MIKU TEAM

05 / Fast Assembly

You can prepare for your first riding after simple 2-step assembly.



Step : Fasten mirrors on the fixing holes at steering bar and tighten with a wrench.



Step : Adjust mirrors in proper position.





06/Pre-Ride Checklist



10

WARNING! Always perform the entire pre-ride checklist before using the scooter as this can help you spot problems that could interfere with safe scooter operation. Failure to follow this entire checklist before every ride can cause death, serious injury, and/or property damage to yourself and/or others.



Ignition Switch



S OFF Position

This position is used to turn the scooter



ON Position

This position is used for operating the scooter. Install the key and turn clockwise. At this position the following sequence occurs: Lights turn ON Dashboard turns ON



A To Operate The Steering Lock:

. Turn the handlebar all the way to the left. . With the key in the OFF position, push the key down and turn the key counter-clockwise.

To unlock the steering lock:

. Install the key and turn clockwise.



Alarm Sound the alarm for tracking position of the scooter.

@ Lock Turn on anti-theft system.

@ Unlock

Turn off anti-theft system.



Brake Levers & Throttle



- Rear brake lever : When stopping the scooter, squeeze the left brake lever smoothly and firmly to engage the
 rear brake Always engage the rear brake first.
- Front brake lever 6: Squeeze the right lever to engage the front brake. The right lever must be squeezed gently
 at first to avoid locking the front wheel.
- Throttle grip : The rotary throttle grip is on the right handlebar. Accelerate by rotating the throttle towards
 you. Decelerate by rotating the throttle away from you. The throttle includes a safety spring that snaps the throttle
 back to end when released.



DANGER!

Use extreme caution when engaging the front brake to avoid locking the front wheel. Locking the front wheel can cause a serious accident.

Left&Right Switch



Left switch

- High & low beam
- Turn signal
- Hom



Right switch

- ∃ speed control key : I:ECO, II:Normal, III:Sport
- Headlight switch

operation.

- O Cruise control key:
 - The speed will be kept without throttle by press Cruise control key.

 The cruise performance will be canceled by any braking





Dashboard



- Davlight Indicator
- @ Energy level indicator Speedometer
- Left turn signal indicator
- @ Riding time indicator
- High beam indicator
- Total odometer A Trip odometer

Right turn signal

@ Energy level indicator

This indicator and readout displays the amount of energy remaining in the power pack, similar to the fuel gauge on a gasoline powered scooter.

Speedometer

Daylight Indicator

When the scooter is starting, the daylight indicator is turned on automatically.

Left turn signal indicator

Flashes green when a left turn is selected by the turn signal switch. This arrow remains flashing until the turn signal request has been canceled.

Riding time indicator

The clock displays riding time of single trip.

(a) High beam indicator

When the headlight high beam is on, this indicator illuminates blue, and remains on until the high beam is turned off.

@ Right turn signal

Flashes green when a right turn is selected by the turn signal switch. This remains flashing until the turn signal request has

Total odometer

The total odometer displays the total distance the scooter has been ridden in kilometers.

@ Trip odometer

The trip odometer displays the distance of single riding in



Before Starting the Engine/Motor

e Tires

Ensure that both tires have at least 1/8 inch tread depth at center.

 Both tires must be inflated to the pressure indicated on the tire sidewalls. • Replace the tires if tread height is less than 1/8 inch at the center of tires.

Throttle

Check for smooth operation. Make sure throttle grip could return to cut off power.

 Check for frayed cable or damaged cable housing. Replace damaged cable to avoid electricity shock. Check for mud, debris and ice in the throttle mechanism, Clean out any contamination.

Fasteners

Check that all axle nuts and lug nuts are secure.

6 Check for missing fasteners. Replace as necessary.

Check that all other fasteners are secure. Tighten as necessary.

Steering

16

Make sure steering turns freely.

Check for proper "toe-in" of wheels

Lubricate/Adjust as necessary. See the Maintenance section.

. Chassis frame Check for bent/damaged components. Replace as necessary.

. Battery Check the power level to ensure it's enough for riding.

. Lights Check for proper operation. Replace bulbs as necessary.

Shutting off the scooter

Always shut off the scooter by turning the ignition switch to OFF.



CAUTION: Squeeze brake lever will shut off the motor, however leaving the ignition switch at the ON position could drain the battery

Stopping the scooter



DANGER! Wet, oily, or sandy roads reduce braking effectiveness. Hard braking on these surfaces could lead to loss of control and a serious accident. Always reduce speed as gradually as possible.

When braking, always engage the rear brake first to retain maximum control of the scooter. Most of your stopping power comes from the front wheel.

Parking

Always keep the key in the lock position when parking the scooter to side stand whenever possible.

The side stand is combined with parking stop switch. The parking stop switch will cut off the power of the motor while the side stand is released.





Motor safety



Keep the scooter free of dirt and debris , especially in the throttle linkage area.

Never start the engine or motor unless

you are property seated with your

hands firmly on the controls.



Never tamper with , alter , or change the scooter motor settings. The motor governor is factory set and protects Excessive motor speed is potentially dangerous to the operator by standers . #7









a loss of control and possible injury or death.





Battery charging





Check the local civil electricity power supply before battery charging.Make sure the battery charger is matched with the power supply.



Always use a Miku original battery charger from manufacturer. Improper charger might pose a fire or explosion risk.





The battery is fully charged, while the state light on the charger turns green.





07/Power Pack & Charging

Miku Max holds a portable power pack in the battery case at the bottom of the scooter.

The power pack could be charged in the scooter or separately charged out of the scooter.



Charging on battery

- . Take out the power pack from the battery case:
- Connect the charger plug to the charging socket on the power pack:
- The charging is in process if the charging indicators are on.



Charging on scooter

- Connect the charger plug to the charging
- socket on the scooter;
- The charging is in process if the red charging indicator on the charger are on.





Take the Power pack out

- Pull the button at the bottom of storage case to open the bottom case;
- Disconnect the wire and take the power pack out.





BATTERY POWER INDICATOR INSTRUCTIONS

The battery is located within the power pack and requires no special break in period.



- . The power indicators show 5 levels of battery power. Each indicator show 20% of battery power
- . The power indicators are blinking while the battery is under charging.
- . The power pack is fully charged while 5 power indicators are all staying on.

08/Maintenance Tips

If you own a MIKU electric scooter you should know there are many things that can go wrong with you electric scooter to hinder its performance. That is why the way you care for your electric scooter is so



Never wash or operate the scooter in freezing temperatures. Water can freeze in wire and the throttle mechanism , possibly resulting in throttle sticking, which can cause the motor to continue to run and result in loss of control



Assembly , maintenance and/or repair of this scooter should only be performed by designated dealers or authorized repair centers for e-scooter repairs Authorized

to ensure quality work and safe scooter conditions.




While stopping always shut off the scooter to aviod move unexpectedly.







Item	Purpose	Rate
Brake	Check braking performance, prevent traffic accident due to braking malfunction	Daily
Tyre	Check tyre damage & air pressure, prevent flat tyre or power overconsumption during driving	Daily
Rim	Check rim strength & remove dirt in bearing, prevent rim breaking or jamming	Weekly
Shock absorber	Check front & rear shock absorbers, remove dirt & maintain lubrication, prevent shock absorber jamming	Weekly
gnition & throttle	Check ignition & throttle, prevent jamming or occasional failure	Weekly
Wire	Check wire connector loose or damage, prevent wire malfunction	Weekly
Screw	Check wire connector loose or damage, prevent wire malfunction	Monthly
Battery	Check battery appearance & cell performance, prevent wire malfunction & lengthen lifespan	Monthly
Charger	Check whether charger wire damage, braking, off-line, input & output connector complete and reliable or not	Monthly
Lubrication	Check front wheel axle, brake need to add lubrication or not	Monthly
Cleaning	Surface cleaning	Monthly





Serial No:



The vehicle identification number (VIN) is required for all warranty work , theft recovery , and consumer safety. The complete VIN also appears on a plate at the bottom of classis frame.

DESIHNED BY MIKU TEAM 2019.1V