



# Legend™ Thermal Tie-On Cable Labels

Made from a durable polyester, these labels are ideal for internal applications such as sub-stations and control rooms. (Also see Legend Laser range in A4 sheets)

Print via Fox-in-a-Box® thermal printer using "One One One" as for all our range of thermal labels using the Basic / Advanced / Professional.

How many labels can be printed from one ribbon?

A 300m thermal ribbon (full width) will yield approx. 16,00 labels.

## TESTING

Test	Method
Elevated Temperature *	MIL-STD-202G Method 108A - 2000 hrs @ 70°C to 100°C
Low Temperature	MIL-STD-810F Method 502.4 - 72 hrs @ 40°C
H2S Sour Gas	Exposure (2% H2S)
Salt Mist Spray	EC60068-2-52 Test Kb Salt Mist (Cyclic)

\*Samples were subjected to 500 hrs @ 70°C, followed by 500 hrs @ 85°C, then 1000 hrs @ 100°C

## TECHNICAL DATA

Printing method:	DTP-1 Printer
Thermal Ribbon:	TSR3
Material:	Polyester
Thickness:	175 micron
RoHS:	Yes
Reach:	Yes



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)

Legend™, Fox-in-a-Box® are registered Trademarks of Silver Fox Group Limited, Licensed to Silver Fox Limited -© Silver Fox Limited, 2023

Copyright © Silver Fox | 2023 Version 3



# Legend™ Thermal Tie-On Cable Labels

## Additional Information

### FEATURES & BENEFITS

- Easy to use and apply
- Pre-perforated for rapid removal from roll
- Apply to any cable from OD Ø 10mm – unlimited
- Choice of two colours and six sizes

## ORDER INFORMATION

Product Code	Label	Labels	Rolls		Colour
	Dims (mm)	Per Roll	per Pack	Labels per pack	
LS6013T	60 x 13	3000	1	3000	● ○
LM9013T	90 x 13	3000	1	3000	● ○
LXL9020T	90 x 20	3000	1	3000	● ○



## STORAGE INSTRUCTIONS

Storage Instructions	Store between 50°F (10°C) and 77°F (25°C)
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. E&OE.



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)

Legend™, Fox-in-a-Box® are registered Trademarks of Silver Fox Group Limited, Licensed to Silver Fox Limited –© Silver Fox Limited, 2023

Copyright © Silver Fox | 2023 Version 3