

Prolab[®] High Performance Tape

Silver Fox's Prolab® High Performance Tape delivers a robust and long-lasting bond due to the solvent permanent adhesive. This HPT label is ideal for general commercial applications.

Choose from an range of colours and sizes to create labelling that aligns perfectly with your businesses needs.

Available in 100mm, 50mm and 25mm and a length of 50mtrs in Yellow and White.

Additional colour oprions are available on request with a minimum order quantity(MOQ)

Example *specify colour eg P/HPT/A/050(100)TW

Barcoding/QR Coding/Graphics functionality is available via the Professional level Fox-in-a-Box®




This high performace tape deliveres a strong long-lasting adhesion to a wide variety of substrates except PE & PP BGVV compliance (indirect food contact)

Print using the Fox-in-a-Box®

Like all of Silver Fox's thermal label range, the **Prolab® High Performace Tape** can be rapidly printed via the Fox-in-a-Box® thermal printer using just "**One software, One Printer, One Ribbon**" with no change of hardware required.



Test	Method		
Resistance to solvents	MIL-STD-202- 215 ω/change 1		
Fire Resistance	DIN EN 13501-1		
TECHNICAL DATA			
Material	PVC film with solvent permanent adhesive		
Dimensional Stability (FINAT TM 14)	Adhered to steel shrinkage 0.15mm max		
Temperature Resistance	Adhered to aluminum -50°C to +120°C		
Sea Water Resistance (DIN EN ISO 9227)	Adhered to aluminum, after 100hrs/35°C no variation		
Resistance to solvents and chemicals	At room temperature, 72hrs after adhesion to aluminium, short-term resistant to most oils & greases, fuels, aliphatic solvents, week acids, salts and alkalis		
Adhesive Power (FINAT TM 1, after 24h, sta	18 N/25 mm inless steel)		







Prolab[®] High Performance Tape

Additional Information

Prolab® High-Performance Tape available with a high gloss finished surface thats delivers clarity to the printed label.

With our Fox-in-a-Box® thermal printer you can print 100mm per second saving you time and resources.

To achieve the best printing results, we recommend using a Fox-in-a-Box® DTP-1 thermal printer along with TSR3/300 thermal transfer ribbon.

Colour	sRGB
White	239,242,242
Yellow	250,196,0
Blue	7,49,173
Red	193,6,26
Green	0,116,71
Orange	239,86,0
Black	14,13,13
Light Brown	224,202,149
Grey	138,143,140

ORDER INFORMATION

	Width	Length		
Product Code	(mm)	(m)	Pack Qty	Colours*
P/HPT/A/025(200)T*	25	200	4 Rolls	
P/HPT/A/050(100)T*	50	100	2 Rolls	
P/HPT/A/100(050)T*	100	50	1 Roll	

*Additional colours available on request with MOQ - specify eg P/HPT/A/050(100)TW



STORAGE INSTRUCTIONS

Storage Instructions	Store between 50°F (10°C) and 77°F (25°C)
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. ESGE.



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Prolab®, Labacus Innovator® and Fox-in-a-Box® are registered Trademarks of Silver Fox Group Limited, Licensed to Silver Fox Limited -© Silver Fox Limited, 2023