



# Prolab<sup>®</sup> Wrap Around Labels

The polyethylene self-laminating wrap round labels are ideal for data cabling.

Print via Fox-in-a-Box<sup>®</sup> thermal printer using "One One One" as for all our range of thermal labels using the Basic / Advanced / Professional.

As a guide, a 300m thermal ribbon (full width) will yield up to 30,000 labels depending on label size.

## TECHNICAL DATA

Printing method:	DTP-1 Printer
Thermal Ribbon:	TSR3
Material:	Polyethylene
Thickness:	105 micron
RoHS:	Yes
Reach:	Yes

## TESTING

Test	Method
Elevated Temperature *	MIL-STD-202G Method 108A - 2000 hrs @ 70oC to 100°C
Low Temperature	MIL-STD-810F Method 502.4 - 72 hrs @ 40°C
H2S Sour Gas	Exposure (2% H2S)
Salt Mist Spray	EC60068-2-52 Test Kb Salt Mist (Cyclic)
UV Weathering	ISO 4982 Part 3 Method A Cycle 1 - 500 hrs

\* Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)

Prolab<sup>®</sup>, Labacus Innovator<sup>®</sup> and Fox-in-a-Box<sup>®</sup> are registered Trademarks of Silver Fox Group Limited, Licensed to Silver Fox Limited -© Silver Fox Limited, 2023

Copyright © Silver Fox | 2023 Version 2





# Prolab<sup>®</sup> Wrap Around Labels

## Additional Information

### FEATURES & BENEFITS

They incorporate a strong, long lasting acrylic adhesive. Typical applications would be industrial Ethernet, data centres etc. Barcoding/QR Coding/ Graphics functionality is available via the Professional level Fox-in-a-Box<sup>®</sup>.

Print via Fox-in-a-Box<sup>®</sup> thermal printer using "One One One" as for all our range of thermal labels.

By choosing the labels with the deeper print areas such as P06/2519T this allows you to print your ID all around a 6 mm wide cable.

## ORDER INFORMATION

Product Code	Cable OD Ø (mm)	Printable Area (mm)	Labels per Roll	Unit Quantity	Colours*
PSA1/07/2512T	5 - 7	25 x 12	5000	1 roll	○
PSA1/06/2519T	5 - 6	25 x 19	5000	1 roll	○ ● ● ●
PSA1/08/2524T	5 - 8	25 x 24	5000	1 roll	○



## STORAGE INSTRUCTIONS

Storage Instructions	Store between 50°F (10°C) and 77°F (25°C)
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. E&OE.

For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)



Prolab<sup>®</sup>, Labacus Innovator<sup>®</sup> and Fox-in-a-Box<sup>®</sup> are registered Trademarks of Silver Fox Group Limited, Licensed to Silver Fox Limited -© Silver Fox Limited, 2023

Copyright © Silver Fox | 2023 Version 2