

2 t Weight Class Mini Excavators *

	Bobcat E20	Takeuchi TB216	Caterpillar 301.7 CR	Kubota U17-HGS	Yanmar ViO17-A
Warranty	2 year/ 2000 hrs	2 year/ 2000 hrs	2 year/ 2000 hrs	2 year/ 2000 hrs	4 year/ 4000 hrs
Tail Swing Design	Zero Tail	Conventional (16.7")	Zero Tail	Zero Tail	Zero Tail
OPERATING PERFORMANCE					
Operating Weight	4,306 lb	3,900 lb	4,167 lb	3,814 lb	3,836 lbs
Max. Bucket Breakout Force	4,684 lbf	4,250 lbf	3,641.9 lbf	3,417.2 lbf	3,418 lbf
Max. Arm Digging Force	2,086 lbf	1,843 lbf	2,135.7 lbf	1,918 lbf	1,918 lbf
Travel Speed - Low	1.3 mph	1.4 mph	1.8 mph	1.4 mph	1.3 mph
Travel Speed - High	2.6 mph	2.6 mph	2.7 mph	2.6 mph	2.7 mph
HYDRAULIC SYSTEM					
Auxiliary Hydraulic Flow	7.9 gpm	8.9 gpm	8.7 gpm	7.32 gpm	8.1 gpm
Hydraulic System Pressure	2,610 psi	3,046 psi	3,553.4 psi	NP	2,625 psi
ENGINE					
Make / Model	Kubota / D722-E4B-BCZ-7	Yanmar / 3TNV74	Cat / C1.1	Kubota / D902-E4	Yanmar / 3TNV74F-SPBV
Displacement	43.88 cu in	60.6 cu in	69 cu in	54.8 cu in	60.6 cu in
Net Horsepower @ max gov rpm	13.9 hp @ 2,500 rpm	15 hp @ 2,400 rpm	21 hp @ 2,400 rpm	15.2 hp @ 2,300 rpm	14.5 hp @ 2,400 rpm
FLUID CAPACITIES					
Fuel Tank Capacity	5 gal	5.8 gal	5.8 gal	5.02 gal	5.3 gal
MACHINE DIMENSIONS					
Maximum Reach at Ground Level	14 ft	13 ft 3 in	12 ft 9.5 in	12 ft 7 in	12 ft
Maximum Digging Depth	8 ft 5 in	7 ft 10 in	7 ft 8.5 in	7 ft 7 in	7 ft 3 in
Maximum Dumping Height	8 ft 8 in	8 ft 10.5 in	8 ft 0.5 in	8 ft 0 in	8 ft 8 in
Transport Length	12 ft 1.2 in	12 ft 8.3 in	11 ft 10.5 in	11 ft 7 in	11 ft 4 in
Transport Height	7 ft 6.4 in	7 ft 5.8 in	7 ft 6.6 in	7 ft 8 in	7 ft 7 in
Undercarriage Width - Track Retracted	39 in	38.6 in	39 in	39 in	37.4 in
Undercarriage Width - Track Extended	53.5 in	51.2 in	51.2 in	48.8 in	50.4 in
LINK TO OFFICIAL SPECIFICATION	Download	Download	Download	Download	Download

* parameters listed here are based on the specs published for US/Canada

2 t Weight Class Mini Excavators *

	Kubota KX018-4	Caterpillar 301.5	Case CX17C	John Deere 17G	Hyundai R17Z-9A
Warranty	2 year/ 2000 hrs	2 year/ 2000 hrs	2 year/ 3000 hrs	2 year/ 2000 hrs	3 year/ 3000 hrs
Tail Swing Design	Conventional (17.7")	Short Tail (6.7")	Zero Tail	Short Tail (1.6")	Zero Tail
OPERATING PERFORMANCE					
Operating Weight	3,967 lb	3,836 lb	3,910 lb	3,790 lbs	3,747 lbs
Max. Bucket Breakout Force	3,594 lbf	3,169.8 lbf	3,490 lbf	3,597 lbf	3,490 lbf
Max. Arm Digging Force	1,852 lbf	1,843.4 lbf	1,920 lbf	1,933 lbf	1,920 lbf
Travel Speed - Low	1.4 mph	1.8 mph	1.4 mph	1.5 mph	1.4 mph
Travel Speed - High	2.6 mph	2.7 mph	2.6 mph	2.6 mph	2.5 mph
HYDRAULIC SYSTEM					
Auxiliary Hydraulic Flow	7.4 gpm	8.7 gpm	7.2 gpm	7.9 gpm	NP
Hydraulic System Pressure	NP	3,089.3 psi	2,466 psi	NP	NP
ENGINE					
Make / Model	Kubota / D902-BH-E4	Cat / C1.1	Kubota / D902	Yanmar / 3TNV74F	Kubota / D902
Displacement	54.8 cu in	69 cu in	54.8 cu in	61 cu in	54.8 cu in
Net Horsepower @ max gov rpm	15.2 hp @ 2,300 rpm	21 hp @ 2,400 rpm	15.8 hp @ 2,300 rpm	14.5 hp @ 2,400 rpm	15.8 hp @ 2,300 rpm
FLUID CAPACITIES					
Fuel Tank Capacity	5.6 gal	5.8 gal	5.3 gal	5.3 gal	5.3 gal
MACHINE DIMENSIONS					
Maximum Reach at Ground Level	12 ft 8 in	12 ft 2.9 in	12 ft 6 in	12 ft 4 in	12 ft 4 in
Maximum Digging Depth	7 ft 9.7 in	7 ft 8.1 in	7 ft 3 in	7 ft 2 in	7 ft 2 in
Maximum Dumping Height	7 ft 9.7 in	8 ft 0.5 in	8 ft 5 in	8 ft 3 in	8 ft 4 in
Transport Length	12 ft 2.1 in	11 ft 10.5 in	11 ft 5 in	11 ft 6 in	11 ft 4 in
Transport Height	7 ft 7.7 in	7 ft 6.9 in	7 ft 7 in	7 ft 10 in.	7 ft 7 in
Undercarriage Width - Track Retracted	39 in	39 in	39 in	38.6 in	39 in
Undercarriage Width - Track Extended	51.2 in	51.18 in	51.2 in	50.4 in	51.2 in
LINK TO OFFICIAL SPECIFICATION	Download	Download	Download	Download	Download

* parameters listed here are based on the specs published for US/Canada