

3 t (2.7-3.0 t) Weight Class Mini Excavators *

	Bobcat E26	Takeuchi TB230	Case CX30C	Kubota KX030-4	Cat 302.7D CR
Warranty	2 Year/ 2,000 hrs	2 year/ 2,000 hrs	2 Year/ 3,000 hrs	2 year/ 2,000 hrs	2 year/ 2,000 hrs
Tail Swing Design	Compact / 3.5 in	Conventional / 20.3 in	Zero	Conventional / 17.7 in	Zero
Cabin and Canopy	Yes	No	Yes	Yes	Yes
OPERATING PERFORMANCE					
Operating Weight (Canopy)	6,489 lb	6,360 lb	6,306 lb	6,272 lb	6,034 lb
Operating Weight (Cab)	N/P	N/A	6,636 lb	6,426 lb	6,239 lb
Max. Bucket Breakout Force	5,652 lbf	6,471 lbf	4,520 lbf	6,924 lbf	5,058 lbf
Max. Arm Digging Force	3,547 lbf	2,900 lbf	3,080 lbf	3,484 lbf	3,462 lbf
Travel Speed - Low	1.8 mph	1.8 mph	1.5 mph	1.7 mph	1.30 mph
Travel Speed - High	3.2 mph	3.2 mph	2.7 mph	2.7 mph	2.36 mph
HYDRAULIC SYSTEM					
Auxiliary Hydraulic Flow	14.2 gpm	13.4 gpm	12.2 gpm	13.1 gpm	13.8 gpm
Hydraulic System Pressure	2,611 psi	3,046 psi	3,133 psi	N/P	3,263 psi
ENGINE					
Model / Make	Kubota / D1105-E4B	Yanmar / 3TNV88F	Kubota / D1305	Kubota / V1505-E4-BH	Yanmar / 3TNV76
Displacement	68.5 cu in	81.0 cu in	77.0 cu in	91.41 cu in	68 cu in
Net Horsepower @ max gov rpm	24.8 hp @ 2,200 rpm	24.4 hp @ 2,400 rpm	23.2 hp @ 2,300 rpm	23.7 hp @ 2,250 rpm	20.7 hp
FLUID CAPACITIES					
Fuel Tank Capacity	9.1 gal	14.0 gal	7.9 gal	12.7 gal	9.3 gal
MACHINE DIMENSIONS					
Maximum Reach at Ground Level	16 ft	15 ft 5.4 in	14 ft 10 in	15 ft 9 in	14 ft 8 in
Maximum Digging Depth	9 ft 6 in	9 ft 3.6 in	8 ft 2 in	9 ft 7 in	8 ft 4 in
Maximum Dumping Height	10 ft 5 in	10 ft 7.2 in	9 ft 7 in	10 ft 4 in	9 ft 4 in
Transport Length	14 ft 2.4 in	15 ft 0.9 in	13 ft 9 in	15 ft 1.1 in	14 ft 0 in
Transport Height	8 ft	8 ft 3.9 in	8 ft 2 in	7 ft 11 in	7 ft 11 in
Undercarriage Width - Track Retracted	N/A	N/A	N/A	N/A	N/A
Undercarriage Width - Track Extended	61.0 in	57.1 in	61 in	59.1 in	61.8 in
LINK TO OFFICIAL SPECIFICATION	Download	Download	Download	Download	Download

* parameters listed here are based on the specs published for US/Canada