



INSTALLATION INSTRUCTIONS

www.vikingbags.com



888-208-1949 |



support@vikingbags.com

VIKING HORIZONTAL STITCH SWINGARM BAG INSTRUCTION

Parts

Swingarm Bag
Mounting Straps x 3

Instructions

Step 1

With bike placed on a level surface, hold the swingarm bag against the swingarm to find out the best position to mount the bag.

Step 2

Remove the battery cover.

Step 3

Hold the bag in the previously determined position and from inside, route a strap through the bottom slot of the top mounting point on the back of the bag. Route the strap around the top bar and then insert the strap back into the bag using the top slot of the top mounting point.

Step 4

Repeat step 3 for the other top mounting point.

Step 5

From inside, route a strap through bottom hole of the bottom mounting point on the back of the bag. Route the strap around the swingarm and insert it back into the bag using the top slot of the top mounting point.

Step 6

Buckle the straps from the inside securely. Make sure straps do not interfere with any moving parts of the bike.

⚠ Warnings

- ✓ Make sure straps do not interfere with any moving parts of the bike
- ✓ If you are not sure about the installation of the saddlebags, do not use them.
- ✓ Sporadically check for shifting of the bag and verify that no part of the mounting system is interfering with any part of the motorcycle while riding. This includes the drive train, suspension, brakes or wheels.
- ✓ Riding with improperly installed bags can lead to fatal accidents.