

TRADE Catalog

2023-24



**BIS
APPROVED**





ABOUT US

Our Lighting Products demonstrates how an everyday object can become a work of Art.

At EcoEarth we have fully embraced the possibility of Led lighting. It has taken hundreds of man hours and some of the brightest minds in the industry to design and develop a new range of lighting products that truly harnesses the technology. The products are designed and manufactured inhouse by the group companies with the idea to be cost effective and look aesthetically crafted.

The result simply shines with beauty and Energy - bright light, streaming through aesthetic, energy efficient structures; products fabricated with deep conviction to meet the most stringent lighting standard.

More than this, we have carefully made our LED lighting designed in a way that they complement their surrounding making all kind of environment safer, more salubrious and sustainable. Our products are already enhancing cities, car parks, industries, hotels and homes, improving the quality of life of millions of people around the world.

We use Energy responsibly and intelligently. Our Advanced Led Systems give you more light for less energy consumed, saving Carbon and Cost. They are built to last a life span greater than 50000 hrs.



They stay cool so they are safer in public spaces and don't emit harmful infrared or ultraviolet rays. We have worked on some ingenious new ways of directing light exactly where it is wanted with minimum glare or overspill.

We have taken our design cues from universe and that is reflected in elegant flowing lines, redefined finishing and the material used in our light systems. Our Sleek luminaries are a work of art and objects of desire in their own right.

We have categorized our LED products with a dedicated name given to each one of them, and each product is worked upon to make better every year with new versions upgrading the previous ones. Each EcoEarth packaging follows a color code dedicated to a particular wattage so that it is easily recognized.

The EcoEarth Advantage

We are not just about product supply, we have the expertise and enthusiasm to help our clients with design and planning all the way to the installation of LED products. We can help with you with this novel technology and guide you through which products are right for you. We calculate payback periods and highlight the cost benefit analysis on LED installations as well.





OVER 65000 SQFT. MANUFACTURING FACILITY CURUGAM, HARYANA



RESEARCH & DEVELOPMENT UNIT



LED DRIVER & PCB ASSEMBLY



ASSEMBLY UNIT



SMT UNIT



DESIGN CENTRE



IN PROCESS CHECKING



ASSEMBLY UNIT



ASSEMBLY UNIT



100% PRODUCT AGEING



2X2 PANEL AGEING



IN-PROCESS PRODUCTS



PROFILE EXTRUSION UNIT



INJECTION MOLDING



METAL STAMPING

Salient Features of the led Smart lights



16 Million Colors
Shades of White + Dimmable



Control your Lights
from Anywhere



Tunable White
Shades of White + Dimmable



Family Sharing



Sync with Music mode



Set Schedule & Timer



App Control



Works with any
Wi-Fi Router



Group Devices



Products Certified with
BIS Quality & Safety
Parametres



Works with
amazon alexa



Works with
Google Assistant



Brightness
Adjustment

EcoEarth

neo

smart

App Operated Smart Lighting Solutions

Your Mood Your Light

COLOR & TUNABLE WHITE LIGHT





TUNABLE WHITE LIGHT



www.ecoearthlighting.com



SWITCH ON | DIM | SET COLOR | SWITCH OFF




WIFI CONNECTED LIGHTS THAT CAN BE GROUP TOGETHER AND ARE OPERATED THROUGH ECOEARTH NEO MOBILE APP. ALSO, CAN BE PAIRED TO WORK WITH GOOGLE HOME & AMAZON ECHO

BULBS | BATTENS | DOWNLIGHTERS | PENDANT LAMPS



Command your lights with your voice



neo

smarter lighting



Wi-fi Enabled Luminaries




NEO Wi-Fi SMART LED PANEL TUNABLE WHITE LIGHT

- Shades of white & Dimmable
- App Control, Inbuilt driver
- Group Devices
- Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Height (H)	Cutout (Round)	Cutout (Square)
10W	115mmx115mm	36 mm	Ø99mm/3.9inch	99mmx99mm(3.9inch)
15W	168mmx168mm	36 mm	Ø149mm/5.9inch	149mmx149mm(5.9inch)

-Available Shape-
(RD & SQ)
-Available Wattage-
10W -15W



TUNABLE WHITE LIGHT



-Available Wattage-
10W-15W

TUNABLE WHITE LIGHT



NEO Wi-Fi SMART LED SURFACE TUNABLE WHITE LIGHT

- Shades of white & Dimmable
- App Control
- Group Devices & Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant.
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Height (H)	Mounting (M)
10W	Ø96mm	50mm	Ø48mm/1.88 inch
15W	Ø148mm	47mm	Ø48mm/1.88 inch



NEO Wi-Fi SMART LED WALL BATTEN TUNABLE WHITE LIGHT

- Shades of white & Dimmable
- App Control
- Group Devices
- Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant.
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Width(H)	Height (C)
20W	4 feet	22 mm	36 mm



-Available Wattage-
20W

TUNABLE WHITE LIGHT



NEO Wi-Fi SMART LED TRIMLESS COB TUNABLE WHITE LIGHT

- Shades of white & Dimmable
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Set Schedule-On/off timers can be set for scheduling your day
- App Control
- Group Devices & Family Sharing
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Rhythm features & Do Not Disturb

TUNABLE WHITE LIGHT



Rated Wattage	Length (L)	Height (H)	Cutout (C)
6W	Ø69 mm	65 mm	Ø57 mm/2.24 inch
12W	Ø84.5 mm	75 mm	Ø75 mm/2.95 inch
18W	Ø95 mm	97 mm	Ø85 mm/3.3 inch



-Available Wattage-
6W | 12W | 18W

NEO Wi-Fi SMART LED TRIMLESS COB TUNEABLE WHITE LIGHT

- Voice Control
- Group Devices
- Set Schedule-Timeout Enable
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Dimmable Light
- App Control
- Family Sharing

-Available Reflector in White Housing-
Black Reflector | Gold Reflector | Nickle Reflector

TUNABLE WHITE LIGHT



-Available Wattage-
12W

-Available Reflector in Black Housing-
Black Reflector | Copper Reflector | Nickle Reflector

Rated Wattage	Length (L)	Height (H)	Cutout (C)
12W	Ø84.5 mm	65 mm	Ø75 mm/2.95 inch



NEO Wi-Fi SMART LED SKYLIGHT TUNABLE WHITE LIGHT

- Shades of white & Dimmable
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Set Schedule-On/off timers can be set for scheduling your day
- App Control
- Group Devices & Family Sharing
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Height (H)
15W	380mm	185mm

-Available Wattage-
15W

TUNABLE WHITE LIGHT



WORKS WITH
amazon alexa

WORKS WITH
Google Assistant

PENDANT HOLDER INCLUDED



PENDANT HOLDER INCLUDED



-Available Wattage-
10W

COLOR & TUNABLE WHITE LIGHT



WORKS WITH
amazon alexa

WORKS WITH
Google Assistant

NEO Wi-Fi SMART SKYLIGHT COLOR+TUNABLE WHITE LIGHT

- 16 Millions of colours - HD Colour rendering with RGB, & Shades of White
- App Control, Group Devices & Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Sync with music : Play music on the phone, and the lights can follow.
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Height (H)
10W	330mm	160mm

NEO Wi-Fi SMART LED PANEL DIMMABLE LIGHT (RD & SQ)

- Voice Control
- App Control
- Group Devices
- Family Sharing
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Dimmable Light



DIMMABLE LIGHT

Rated Wattage	Length (L)	Height (H)	Cutout (Round)	Cutout (Square)
6W	Ø120 mm	23 mm	Ø105 mm/4.2 inch	105x105 mm/4.2X4.2 inch
9W	Ø148 mm	23 mm	Ø125 mm/5 inch	125x125 mm/5X5 inch
12W	Ø170 mm	23 mm	Ø155 mm/6 inch	155x155 mm/6X6 inch
15W	Ø188 mm	23 mm	Ø172 mm/6.25 inch	172x172 mm/6.7X6.7 inch
18W	Ø222 mm	23 mm	Ø210 mm/8.3 inch	210x210 mm/8.3X8.3 inch
24W	Ø300 mm	23 mm	Ø280 mm/11 inch	280x280 mm/11X11 inch

-Available Wattage-
**6W | 12W | 15W
18W | 24W**


WORKS WITH
amazon alexa

WORKS WITH
Google Assistant



Illuminate your world with
intelligent brilliance.

EcoEarth Smart Wi-Fi LED lights



NEO Wi-Fi SMART LED COLOR + TUNABLE WHITE LAMP

- 16 Millions of colours - HD Colour rendering with RGB, & Shades of white
- App Control
- Group Devices & Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Sync with music : Play music on the phone, and the lights can follow.
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Width (W)	Height (H)
9W	Ø60	60mm	130mm

-Available Wattage-
9W

COLOR & TUNABLE WHITE LIGHT



-Available Wattage-
10W-15W



COLOR & TUNABLE WHITE LIGHT



NEO Wi-Fi SMART LED SURFACE COLOR+TUNABLE LIGHT

- 16 Millions of colours - HD Colour rendering with RGB, & shades of White
- App Control, Group Devices & Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Sync with music : Play music on the phone, and the lights can follow.
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Height (H)	Mounting (M)
10W	Ø96mm	50mm	Ø48mm/1.88 inch
15W	Ø148mm	47mm	Ø48mm/1.88 inch

NEO Wi-Fi SMART LED DOWNLIGHT COLOR + TUNABLE LIGHT

- 16 Millions of colours - HD Colour rendering with RGB, & Shades of White
- App Control
- Group Devices & Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Sync with music : Play music on the phone, and the lights can follow.
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Height (H)	Cutout (C)
9W	Ø115 mm	33 mm	Ø99 mm/3.9 inch
15W	Ø165 mm	33 mm	Ø149 mm/5.9 inch

-Available Wattage-
9W | 15W

COLOR & TUNABLE WHITE LIGHT



NEO Wi-Fi SMART LED WALL BATTEN COLOR + TUNABLE WHITE LIGHT

- 16 Millions of colours - HD Colour rendering with RGB, & Shades of White
- App Control, Group Devices & Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere
- Works with any Wi-Fi Router
- Voice Control: Control lights with your voice using Amazon Alexa & Google Assistant
- Sync with music : Play music on the phone, and the lights can follow.
- Rhythm features & Do Not Disturb

Rated Wattage	Length (L)	Width(H)	Height (C)
20W	4 feet	30 mm	36 mm



-Available Wattage-
20W (4feet)



RF CONTROLLER

LED STRIP COLOR + TUNABLE WHITE LIGHT + RF CONTROLLER

- Perfectly suitable for profile lighting
- 16 Millions of colours - HD Colour rendering with RGB, & Shades of white
- App Control, Group Devices & Family Sharing
- Set Schedule-On/off timers can be set for scheduling your day
- Control your Lights from Anywhere ,Works with any 2.4GHz Wi-Fi Router
- Works with Alexa, Google hm, Siri, Mobile app and RF remote.
- Sync with music : Play music on the phone, and the lights can follow.
- System Lumen > 140lm/W

LED Strip Lights High Quality Double Side PCB 35 Micron Copper Decorative Lighting Indoor Application Cove Light				
Rated Wattage (Per Meter)	LEDs (Per Meter)	Voltage	PCB Width (mm)	Roll Size (Meter)
10W/MTR	5050-60LEDs	12V DC	12	5

NEO BLUETOOTH SMART LED DOWNLIGHT COLOR + TUNABLE LIGHT

- 16 Millions of colours - HD Colour rendering with RGB, Shades of White
- App Control
- Family Sharing
- Group Device
- Sync with music : Play music on the phone, and the lights can follow.

Rated Wattage	Length (L)	Height (H)	Cutout (C)
9W	Ø115 mm	33 mm	Ø99 mm/3.9 inch
15W	Ø165 mm	33 mm	Ø149 mm/5.9 inch



-Available Wattage-
9W | 15W

LED STRIP COLOR + TUNABLE WHITE LIGHT + RF CONTROLLER

- Perfectly suitable for profile lighting
- 16 Millions of colours - HD Colour rendering with RGB, & Shades of white
- RF Remote Controller.
- Works with any 2.4GHz RF Controller
- System Lumen > 140lm/W



RF CONTROLLER



COLOR & TUNABLE WHITE LIGHT



LED Strip Lights High Quality Double Side PCB 35 Micron Copper Decorative Lighting Indoor Application Cove Light				
Rated Wattage (Per Meter)	LEDs (Per Meter)	Voltage	PCB Width (mm)	Roll Size (Meter)
10W/MTR	5050-60LEDs	12V DC	12	5



LED STRIP 240 LEDs

- Perfectly suitable for profile lighting
- Profile strip with 240 LEDs
- 2835 LED is used for better illumination
- Uniform light spread
- Flexible form allows customized lighting shape and design.
- Superior adhesive for easy installation
- To be used with 5A driver for glowing strip.
- System Lumen > 140lm/W

LED Strip Lights High Quality Double Side PCB 35 Micron Copper Decorative Lighting Indoor Application Cove Light				
Rated Wattage (Per Meter)	LEDs (Per Meter)	Voltage	PCB Width (mm)	Roll Size (Meter)
16W/MTR	2835-240LEDs	12V DC	10	5

LED STRIP 120 LEDs

- Perfectly suitable for profile lighting
- Profile strip with 120 LEDs
- 2835 LED is used for better illumination
- Uniform light spread
- Flexible form allows customized lighting shape and design.
- Superior adhesive for easy installation
- To be used with 2A driver for glowing strip.
- System Lumen > 140lm/W



LED Strip Lights High Quality Double Side PCB 35 Micron Copper Decorative Lighting Indoor Application Cove Light				
Rated Wattage (Per Meter)	LEDs (Per Meter)	Voltage	PCB Width (mm)	Roll Size (Meter)
10W/MTR	2835-120LEDs	12V DC	8	5



LED FLAT ROPE LIGHT WITH WIRE

- Profile strip with 120 LEDs
- 2835 LED is used for better illumination
- This LED Rope light can be used both indoors and outdoors.
- Flexible form allows customized lighting shape and design.
- Waterproof with IP65 rating, for superior life and withstanding harsh weather.
- Low power consumption, Safe and Reliable. Looks very Beautiful at night and can be easily installed, Long Life and Perfect for your requirement.
- System Lumen > 140lm/W



2 Amp & 4 Amp
Plug Wire Available

LED Rope Lights High Grade Silicon Housing IP Protection Plug & Play Out of the Box Indoor & Outdoor Applications Cove Light				
Rated Wattage (Per Meter)	LEDs (Per Meter)	Voltage	PCB Width (mm)	Roll Size (Meter)
6W/MTR	2835-120LEDs	220V DC	5	25



LED FLAT ROPE LIGHT DIFFUSED-WIRELESS

- Profile strip with 120 LEDs
- 2835 LED is used for better illumination
- This LED Rope light can be used both indoors and outdoors.
- Flexible form allows customized lighting shape and design.
- Waterproof with IP65 rating, for superior life and withstanding harsh weather.
- Low power consumption, Safe and Reliable. Looks very Beautiful at night and can be easily installed, Long Life and Perfect for your requirement.
- System Lumen > 140lm/W



4 Amp & 8 Amp
Plug Wire Available



LED Rope Lights High Grade Silicon Housing IP Protection Plug & Play Out of the Box Indoor & Outdoor Applications Cove Light				
Rated Wattage (Per Meter)	LEDs (Per Meter)	Voltage	PCB Width (mm)	Roll Size (Meter)
8W/MTR	2835-120LEDs	220V DC	8	45

LED DOB FLAT ROPE LIGHT - HIGH LUMENS

- Perfectly suitable for profile lighting
- Profile strip with 120 LEDs
- 2835 LED is used for better illumination
- This LED Rope light can be used both indoors and outdoors.
- Flexible form allows customized lighting shape and design.
- Superior adhesive for easy installation
- Waterproof with IP65 rating, for superior life and withstanding harsh weather.
- System Lumen > 140lm/W



Direct 220V AC Power Supply
Can be cut at every 10mm

LED Rope Lights High Grade Silicon Housing IP Protection Plug & Play Out of the Box Indoor & Outdoor Applications Cove Light				
Rated Wattage (Per Meter)	LEDs (Per Meter)	Voltage	PCB Width (mm)	Roll Size (Meter)
10W/MTR	2835-60LEDs	220V AC	8	45



INDOOR LIGHTS

Salient Features of the led lights



Higher Lumen Output
Better Efficacy 110lm / Watt



Power Factor
0.95



Wide Voltage
220-240VAC, 50Hz



Energy Saving
85%



Surge Protection
2.5-4.0 KV



Excellent CRI
>80



Life Expectancy
25000 hrs.



Eco-Friendly



No UV & IR
Radiation



Products Certified with
BIS Quality & Safety
Parametres



Zero
Maintenance



Aluminum
head Sink



Anti-glare
Diffuser

ACE LED MINI LAMP (B22/E27/E14)

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.9 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Cap Base	Width (W)	Height (H)
2.9W	B22 E27 E14	Ø36 mm	77 mm



-Available Wattage-
2.9W

**Small Yet
Powerful**



ACE LED FULL DOME LAMP 270° DIFFUSION

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.9 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours

Rated Wattage	Cap Base	Width (W)	Height (H)
7W 9W	B22 E27	Ø60 mm	110 mm
12W	B22 E27	Ø65 mm	125 mm
15W	B22 E27	Ø69 mm	134 mm

-Available Wattage-
**7W | 9W
12W | 15W**

ACE LED HALF DOME LAMP 180° DIFFUSION

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.9 , CRI-80
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours
- High lumen output



Rated Wattage	Cap Base	Width (W)	Height (H)
5W 7W 9W	B22 E27	Ø57 mm	100 mm
12W 15W 18W	B22 E27	Ø65.5 mm	124 mm
20W 26W	B22 E27	Ø80 mm	145 mm



-Available Wattage-
5W-26W

-Available Caps-
B22/E27



ACE LED RGB LAMP 180° DIFFUSION

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.9 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Cap Base	Width (W)	Height (H)
9W	B22 E27	Ø57 mm	100 mm



-Available Wattage-
9W



-Available Wattage-
5W

ACE LED CANDLE LAMP (B22/E27/E14)

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.9 , CRI-80
- Provide high brightness
- Exceedingly high life & lasts upto 15000 hours
- High lumen output



Rated Wattage	Cap Base	Width (W)	Height (H)
5W	B22 E27 E14	Ø36 mm	102 mm

ACE LED CLASSIC CANDLE LAMP (B22/E27/E14)

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.9 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 15000 hours



Rated Wattage	Cap Base	Width (W)	Height (H)
5W	B22 E27 E14	Ø36 mm	102 mm

-Available Wattage-
5W



ACE EMERGENCY LED LAMP (B22/E27)

- Charging Time : 7-8 Hours
- Emergency Time : 4 Hours (Max)
- Lithium Battery: 2200 mAh
- Overcharge and over discharge protection circuit
- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80

 6500K

Rated Wattage	Cap Base	Width (W)	Height (H)
10W	B22	Ø70 mm	139 mm



-Available Wattage-
30W | 40W | 50W



-Available Wattage-
10W

DOME LED LAMP (B22/E27)

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours

  
6500K 4000K 3000K

Rated Wattage	Cap Base	Width (W)	Height (H)
30W	B22 E27	Ø97 mm	170 mm
40W	B22 E27	Ø115 mm	190 mm
50W	B22 E27	Ø137 mm	220 mm

DOME LED HIGH WATTAGE LAMP (B22/E27)

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours

  
6500K 4000K 3000K

Rated Wattage	Cap Base	Width (W)	Height (H)
40W	B22 E27	Ø100 mm	180mm
50W	B22 E27	Ø116 mm	208 mm



-Available Wattage-
40W | 50W

Links 2X2 LED Panel

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Suitable for all Indian Power Conditions
- Provide high brightness
- Provide High Brightness
- Polycarbonate Housing.



Rated Wattage	Size
42W	2X2 Feet

-Available Wattage-
42W



-Available Wattage-
12W | 24W | 50W

HEXA LED WALL BATTEN

- LED Batten with hexagon design & decorative end caps.
- Lm80 testes high brightness LED technology
- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80, High lumen output
- Double color Extruded Profile



Rated Wattage	Length (L)	Width (W)	Height (H)
12W	1 Feet	40mm	31mm
24W	2 Feet	40mm	31mm
50W	4 Feet	40mm	31mm

LUMNEA LED WALL BATTEN

- LED Batten with slim design & decorative end caps.
- Lm80 testes high brightness LED technology
- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Double color Extruded Profile



Rated Wattage	Length (L)	Width (W)	Height (H)
36W	4 Feet	30 mm	36 mm

-Available Wattage-
36W



SHINE LED WALL BATTEN


- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Length (L)	Width (W)	Height (H)
6W	1 Feet	21mm	36mm
12W	2 Feet	21mm	36mm
20W	4 Feet	21mm	36mm
24W	4 Feet	21mm	36mm



-Available Wattage-
6W | 12W | 20W | 24W



-Available Wattage-
20W

PRIME SLIME LED WALL BATTEN

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours
- High lumen output



Rated Wattage	Length (L)	Width (W)	Height (H)
20W	4 Feet	20 mm	33 mm

LINKS LINKABLE LINEAR LED LIGHT

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Length (L)	Width (W)	Height (H)
5W	1 Feet	22mm	36mm
10W	2 Feet	22mm	36mm
20W	4 Feet	22mm	36mm



-Available Wattage-
5W | 10W | 20W

Suspension Kit Available

DUO BACKLIT LED PANEL ROUND

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- Inbuilt driver, Extra Diffusion Area
- High lumen output
- Suitable for all Indian Power Conditions.
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours
- Polycarbonate Housing.

Rated Wattage	Width (W)	Height (H)	Cutout (H)
6W	Ø82mm	36 mm	Ø65mm/2.55inch
10W	Ø115mm	36 mm	Ø99mm/3.9inch
15W	Ø166mm	36 mm	Ø149mm/5.9inch
20W 24W	Ø226mm	36 mm	Ø205mm/8.1inch



-Available Wattage-
6W -24W



Insert Molded Chord
Help of safe handing of
the lights



-Available Wattage-
6W-24W

DUO BACKLIT LED PANEL SQUARE

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- Extra Diffusion Area
- High lumen output
- Suitable for all Indian Power Conditions.
- Provide high brightness
- Polycarbonate Housing.

Rated Wattage	Length (L)	Height (H)	Cutout (H)
6W	82X82mm	36 mm	65mm/2.55X2.55inch
10W	115X115mm	36 mm	99mm/3.9X3.9inch
15W	166X166mm	36 mm	149mm/5.9X5.9inch
20W 24W	226X226mm	36 mm	205mm/8.1X8.1inch

FLEXY LED ADJUSTABLE PANEL

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Suitable for all Indian Power Conditions.
- Provide high brightness
- Polycarbonate Housing.
- Also Fitted in Junction Box & Concealed Box



-Available Wattage-
10W | 15W



Rated Wattage	Width (W)	Height (H)	Mounting (Round)	Mounting (Square)
10W	Ø116mm	37 mm	(Ø60-Ø104)mm/(2.5-4)inch	(60-104)mm/(2.5-4)inch
15W	Ø165mm	37 mm	(Ø60-Ø150)mm/(2.5-6)inch	(60-150)mm/(2.5-6)inch

UNO LED SURFACE STRIKERS DOWNLIGHT

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 2.5 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Width (W)	Height (H)	Mounting (M)
5W	Ø62mm	16.5mm	Ø48mm/1.88

-Available Wattage-
5W



-Available Wattage-
10W | 15W

UNO LED SURFACE DOWNLIGHT

- Also Fitted on Junction Box & Concealed Box
- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness



Rated Wattage	Width (W)	Height (H)	Mounting (M)
10W	Ø96mm	50mm	Ø48mm/1.88 inch
15W	Ø148mm	47mm	Ø48mm/1.88 inch

UNO EMERGENCY SURFACE LIGHT

- Charging Time : 7-8 Hours
- Emergency Time : 4 Hours (Max)
- Lithium Battery: 2200 mAh
- Overcharge and over discharge protection circuit
- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80



Rated Wattage	Width (W)	Height (H)	Mounting (M)
10W	Ø96mm	50mm	Ø48mm/1.88 inch

INVERTER
LED LIGHT
-UPTO-



-Available Wattage-
10W

GALAXY SURFACE DOWNLIGHT (ROUND)

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Length (L)	Height (H)
6W	120X120 mm	37 mm
12W	170X170 mm	37 mm
18W	220X220 mm	37 mm
24W	225X225 mm	37 mm



-Available Wattage-
6W | 12W | 18W | 24W



GALAXY SURFACE LIGHT (SQUARE)

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Suitable for all Indian Power Conditions.
- Provide high brightness
- Polycarbonate Housing.



Rated Wattage	Width (W)	Height (H)
6W	Ø120 mm	37 mm
12W	Ø170 mm	37 mm
18W	Ø220 mm	37 mm
24W	Ø225 mm	37 mm

-Available Wattage-
6W | 12W | 18W | 24W

GALAXY SLIM LED SURFACE DOWNLIGHT (RD & SQ)

- Also Fitted in Junction Box & Concealed Box
- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness



Rated Wattage	Width (W)	Height (H)
12W	Ø140 mm	33 mm
18W	Ø174.5 mm	28 mm



**Changes Color on
EVERY CLICK**


FOCUS LED MINI SPOT DOWNLIGHT (ROUND & SQUARE)

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 2.5 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Suitable for all Indian Power Conditions.
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Width (W)	Height (H)	Cutout (H)
2W	Ø42mm	16.5 mm	Ø38mm/1.49inch

-Available Wattage-
2W



FOCUS LED SPOT DOWNLIGHT

- Lens based LED Down lighter
- Strong Focussed beam
- Latest LED Technology
- 85% energy saving, High lumen output
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80



Rated Wattage	Width (W)	Height (H)	Cutout (H)
4W	Ø74mm	40 mm	Ø54mm/2inch
6W	Ø95mm	47 mm	Ø65mm/2.55inch
9W	Ø116mm	50 mm	Ø85mm/3.34inch
12W	Ø139mm	55 mm	Ø112mm/4.4inch

Black housing Available for Bulk Projects Order



-Available Ring-
Gold | Chrome | White

-Available Wattage-
4W | 6W | 9W | 12W

RIO LED CONCEALED COB DOWNLIGHT

- Lens based COB Down lighter
- Strong Focussed beam
- Latest LED Technology
- Easily Fitted in Junction Box & Concealed Box
- 85% energy saving, High lumen output
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80



Rated Wattage	Width (W)	Height (H)	Cutout (H)
4W	Ø80mm	50mm	Ø52mm/2inch
9W	Ø110mm	64mm	Ø76mm/2.9inch

-Available Wattage-
4W | 9W

-Available -
Black | White



FOCUS TRIMLESS COB DOWNLIGHT

- Beam Angle 36°-38°
- Aluminum Head sink
- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output

6500K 4000K 3000K

Rated Wattage	Width (W)	Height (H)	Cutout (C)
6W	Ø69mm	65mm	Ø57mm/2.24 inch
12W	Ø84.5mm	75mm	Ø75mm/2.95 inch
18W	Ø95mm	97mm	Ø85mm/3.3 inch



-Available Wattage-
12W | 18W | 24W | 36W



-Available Housing-
Black | White

-Available Wattage-
6W | 12W | 18W



FOCUS COB ZOOM LIGHT

- Lens based Zoom light
- Latest LED Technology
- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output

6500K 4000K 3000K

Rated Wattage	Width (W)	Height (H)	Cutout (H)
12W	Ø90mm	73 mm	Ø85mm/3.34inch
18W	Ø110mm	84 mm	Ø100mm/3.93inch
24W	Ø134mm	105 mm	Ø122mm/4.8inch
36W	Ø165mm	135 mm	Ø148mm/5.8inch



-Available Housing-
Black | White

-Available Wattage-
15W | 25W



FOCUS COB TRACK LIGHT

- Lens based Track light
- Latest LED Technology 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours

6500K 4000K 3000K

Rated Wattage	Height (H)
15W	Ø110 mm
25W	Ø130 mm

Track also Available



-Available Housing-
Black | White

-Available Wattage-
15W | 25W



COSMO LINEAR SPOT DOWNLIGHT

- Lens based led Downlighter
- Strong focussed beam
- Latest LED technology
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80 & Provide high brightness
- 85% energy saving, High lumen output
- Suitable for all Indian Power Conditions.
- Polycarbonate Housing.



Rated Wattage	Length (L)	Height (H)	Width (W)	Cutout (H)
5W	77mm	38.1mm	46 mm	(70 x 38)mm/(2.75X1.5) inch
10W	170mm	38.1mm	46 mm	(163x38)mm/6.4X1.5) inch



Inbuilt Driver

-Available Wattage-
5W | 10W



Inbuilt Driver

-Available Wattage-
5W | 10W



Rated Wattage	Length (L)	Height (H)	Width (W)	Cutout (H)
5W	77mm	38.1mm	46 mm	(70 x 38)mm/(2.75X1.5) inch
10W	170mm	38.1mm	46 mm	(163x38)mm/6.4X1.5) inch

COSMO LINEAR LED DOWNLIGHT

- Diffuser based led Downlighter
- Strong focussed beam
- Latest LED technology
- 85% energy saving, High lumen output
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80

BIXY MINI JUNCTION BOX LIGHT

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Suitable for all Indian Power Conditions.
- Provide high brightness
- Polycarbonate Housing.



Rated Wattage	Width (W)	Height (H)	Cutout (Round)	Cutout (Square)
2W	Ø81mm	32 mm	Ø48 mm/1.8 inch	48x48mm/1.8x1.8 inch

-Available Shape-
(RD & SQ)

-Available Wattage-
2W



BIXY MINI DEEP JUNCTION BOX LIGHT

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Suitable for all Indian Power Conditions.
- Provide high brightness
- Polycarbonate Housing.



Rated Wattage	Width (W)	Height (H)	Cutout (C)
3W	Ø80mm	32.5 mm	Ø57 mm/2.2inch



-Available Wattage-
3W

BIXY DEEP JUNCTION BOX LIGHT

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Width (W)	Height (H)	Cutout (C)
4W	Ø80mm	50 mm	Ø52 mm/2 inch



-Available Wattage-
4W

BIXY SLIM CONCEALED DOWNLIGHT

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Width (W)	Height (H)	Cutout (C)
5W	Ø109mm	27 mm	Ø72 mm / 2.8 inch



-Available Wattage-
5W

BIXY CONCEALED DOWNLIGHT

- Also Fitted in Junction Box & Concealed Box
- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness



Rated Wattage	Width (W)	Height (H)	Cutout (C)
6W	Ø110mm	50 mm	Ø74 mm/2.9 inch



-Available Wattage-

6W Fits in 3&4 inch Concealed Box



-Available Wattage-
7W | 9W

Fits in 4 inch Concealed Box

BIXY CONCEALED DOWNLIGHT

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours
- High lumen output



Rated Wattage	Width (W)	Height (H)	Cutout (C)
7W 9W	Ø109mm	65 mm	Ø74 mm/2.9 inch



-Available Wattage-

12W Fits in 4 inch Concealed Box

BIXY CONCEALED DOWNLIGHT

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Width (W)	Height (H)	Cutout (C)
12W	Ø110mm	64 mm	Ø76 mm / 3 inch

BIXY TRICOLOR CONCEALED DOWNLIGHT (3 IN 1)

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- Changes color on **Every Click**
- Suitable for all Indian Power Conditions.
- Provide high brightness
- Polycarbonate Housing.



Rated Wattage	Width (W)	Height (H)	Cutout (C)
6W	Ø109mm	65 mm	Ø74 mm/2.9 inch



Changes Color on
EVERY CLICK

-Available Wattage-
6W

DECO LED DOWNLIGHT

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Width (W)	Height (H)	Cutout (C)
5W	Ø98mm	55 mm	Ø70 mm / 2.7 inch

LED Skylight

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 4.0 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Width (W)	Height (H)
12W	280MM	140MM
18W	430MM	215MM



PENDANT HOLDER INCLUDED

-Available Wattage-
12W | 18W | 24W

The **LINKS** Lighting system from EcoEarth is a Plug & Play system developed to light up your spaces with different shapes formation. These luminaries have inbuilt power supplies and hence are easy to operate and install.

Different shapes of **END CONNECTORS** are available to **Make Any Formation Possible**.


Ideal for Offices, Shopping Malls, Marts, Showrooms, Hotels, Restaurants, Cafes, Hospitals, Homes, Product Displays, Indoor Parkings.

LINKS

Linkable LED Light

Linear Lighting OFFICE

PLUG & PLAY SYSTEM



CCT 2700-6500K	Inbuilt Power Supply	SURGE PROTECTION UPTO 4 kV	FLUCTUATION PROOF Wide Operating Voltage
--------------------------	-----------------------------	--------------------------------------	--

Lengths Available in 1 Feet, 2 Feet, 4 Feet Standard Sizes

Special Sizes upto 8 Feet can be developed as per the bulk Project requirement.



TRIANGLE FORMATION 60°	CONNECTOR 2 Pole 90°	CONNECTOR 3 Pole 90°	CONNECTOR 4 Pole 90°	HEXAGON FORMATION 2 Pole 120°
HEXAGON FORMATION 3 Pole 60°	LINEAR CONNECTOR 2 Pole 180°	2 PIN LEAD WIRE	SUSPENSION KIT 2 CLUTCH WIRE 2 METAL CONNECTORS	

Rated Wattage	Length (L)
5W	1 Feet
10W	2 Feet
20W	4 Feet

	6500K		RED
	4000K		GREEN
	3000K		BLUE


CONNECTOR NAME	ANGLE
TWO POLE CONNECTOR	60°
THREE POLE CONNECTOR	60°
TWO POLE CONNECTOR	90°
THREE POLE CONNECTOR	90°
FOUR POLE CONNECTOR	90°
TWO POLE CONNECTOR	120°
LINEAR CONNECTOR	180°
2 PIN LEAD WIRE CONNECTOR	
SUSPENSION KIT (2 STRINGS + 2 METAL CONNECTORS)	

1 X 4 | Armstrong Panel

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Length (L)	Width (W)
36W	4 Feet	1 Feet
42W	4 Feet	1 Feet



-Available Wattage-
36W | 42W

2X 4 | Armstrong Panel

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Length (L)	Width (W)
60W	4 Feet	2 Feet
72W	4 Feet	2 Feet

-Available Wattage-
60W | 72W

2 X 2 | Backlit Panel

- 85% energy saving over GLS
- Wide voltage range 220-240V, 50Hz
- Surge protection \leq 4.0 KV
- Power factor \geq 0.95, CRI-80
- High lumen output
- Provide high brightness
- Exceedingly high life & lasts upto 25000 hours



Rated Wattage	Length (L)	Width (W)
36W	2 Feet	2 Feet
42W	2 Feet	2 Feet



-Available Wattage-
36W | 42W | 48W



INPUT VOLTAGE
120V-300V, 50Hz

POWER FACTOR
>0.9

EFFICIENCY
> 85%

SURGE PROTECTION
Internal 3 KV
External 10 KV

IP66

CRI>80

OUTDOOR LIGHTS




PRISM LED FLOOD LIGHT

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 10 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- IP66 Protection
- Advance Heatsink

6500K 4000K 3000K

-Available Wattage-
30W | 50W | 100W | 150W | 200W



PRISM LED FLOOD LIGHT

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 10 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- IP66 Protection
- Advance Heatsink
- Efficiency $>85\%$

-Available Wattage-
30W | 50W

6500K 4000K 3000K

PRISM LED STREET LIGHT

- 85% energy saving
- Wide voltage range 220-240V, 50Hz
- Surge protection ≤ 10 KV
- Power factor ≥ 0.95 , CRI-80
- High lumen output
- IP66 Protection
- Advance Heatsink
- Efficiency $>85\%$

6500K 4000K 3000K

-Available Wattage-
20W | 30W | 50W | 100W





INPUT VOLTAGE
120V-300V, 50Hz

POWER FACTOR
>0.9

EFFICIENCY
> 85%

SURGE PROTECTION
Internal 3 KV
External 10 KV

IP66

CRI >80

INDUSTRIAL LIGHTS

PRISM HIGH BAY LIGHT

- Wide voltage range 120-300V, 50Hz
- Surge protection ≤ 10 KV
- High lumen output
- IP66 Protection
- Advance Heatsink
- Efficiency >85%



6500K



-Available Wattage-

50W | 100W | 150W

POWER SUPPLIES FOR STRIP LIGHT

POWER	POWER FACTOR	V _{in}	V _{out}	I _{out}
12W	>0.9	100V - 265V	12V	1A



POWER	POWER FACTOR	V _{in}	V _{out}	I _{out}
24W	>0.9	100V - 265V	12V	2A



POWER	POWER FACTOR	V _{in}	V _{out}	I _{out}
60W	>0.9	100V - 265V	12V	5A



POWER	POWER FACTOR	V _{in}	V _{out}	I _{out}
120W	>0.9	100V - 265V	12V	10A



POWER	POWER FACTOR	V _{in}	V _{out}	I _{out}
180W	>0.9	100V - 265V	12V	15A





Scan the QR Code
to download
EcoEarth's mCatalog



ECO EARTH ELECTRIC PRIVATE LIMITED

CORPORATE OFFICE : Plot No-1, Udyog Vihar,
Phase-6, Near Hero Honda Chowk,
Gurugram, Haryana (INDIA) 122001

Telephone : +91 87507 12345

E-mail : info@ecoearth.ind.in

Whatsapp : +91 98738 78808

www.ecoearthlighting.com

Join us on Facebook at www.facebook.com/EcoEarthlighting/
and share your ways to make life better ahead.