



Affordable **Compact** Desktop Printers for Unrivalled Performance, Convenience & Versatility



Prints 4" Labels, Receipts, Wristbands and Tags



CG4 Series

INDUSTRY VERTICALS

- Healthcare
- Retail
- Transportation & Logistics
- Manufacturing
- Office

APPLICATIONS

- Carton / Package Labelling
- Small Office Mailing
- Shelf-edge labelling
- Product Labelling
- Healthcare Specimen Labelling
- File Folder Labelling

FEATURES

- Supports Input from Keypad
- 203 and 305dpi Print Resolution
- 4MB Flash Memory
- Thermal Transfer and Direct Thermal
- Multiple Codepage Support
- Multiple Printer Language-Compatible Options
- Safety Top Cover Latch

ACCESSORIES



Keypad

- Graphical LCD display
- Alphanumeric and one-touch function keys
- SD card supported
- Enables stand-alone printing (eliminates need to connect to a PC)



Dispenser

- Simplifies separation of labels from a backing paper for immediate label application



Cutter

- Precisely cut individual labels and tags
- Allows continuous printing and cutting of labels and tags

▶ Standalone Capability Using Keypad

- SATO Keypad allows users to Format, Store, Input & Print without connecting to PC
- Label formats can be stored, and called on at time of printing

▶ Flexible Use & Compatibility With Legacy Systems

- 2 Standard Communication Interface configurations: USB and RS232C; or USB and LAN; or USB and Parallel
- Parallel port allows printer to be connected to legacy systems

▶ High Quality Printing

- Suitable for printing graphics and logos, 2D barcodes or patient's photo on wristbands

▶ User-Friendly Operation & Maintenance

- Intuitive label mechanism design allows media loading in 3 simple steps: Drop-Load-Go
- User-friendly maintenance
- The One-touch, tool-less print head release mechanism enables the print head to be quickly and easily replaced
- Printer Platen Roller can be replaced without the need for any tools

▶ Print Labels with Date/Time Stamps Using Real-Time Clock Feature

▶ Compatible

- Printer language options enables replacement of competitive printer models with minimal reprogramming of data streams

General Specifications

CG4



PRINTER MODEL		CG408	CG412
PRINT SPECIFICATIONS			
Print Method		Direct Thermal/Thermal Transfer	
Print Resolution		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max Print Speed		100mm/sec (4ips)	
Max. Print Area		(WxP): 104 x 300mm (4.09" x 11.81")	
CPU		32 Bits RISC-CPU 64MHz	
Printer Body Memory		Main Memory (Flash ROM): 4MB byte, SDRAM: 8MB byte	
MEDIA SPECIFICATIONS			
Sensor Type		I-Mark Sensor (Reflection type), Label Gap Sensor (Transparent type)	
Media	Label Size	Continuous	L: 7 ~ 300mm (0.28" ~ 11.81"), With backing paper: 10 ~ 303mm (0.39" ~ 11.93") W: 22 ~ 107mm (0.87" ~ 4.21"), With backing paper: 25 ~ 110mm (0.98" ~ 4.33")
		Tear-Off	L: 22 ~ 300mm (0.87" ~ 11.81"), With backing paper: 25 ~ 303mm (0.98" ~ 11.93") W: 22 ~ 107mm (0.87" ~ 4.21"), With backing paper: 25 ~ 110mm (0.98" ~ 4.33")
		Label without Adhesive	
	Label Thickness	Continuous	L: 10 ~ 303mm (0.39" x 11.93"), W: 25 ~ 110mm (0.98" x 4.33")
		Tear-Off	L: 25 ~ 303mm (0.98 x 11.93"), W: 25 ~ 110mm (0.98" x 4.33")
	Wind Direction	Face-in/Face-out	
Media Roll Size	Max external diameter: 128mm (5.04"), Paper core inner diameter: 40mm (1.57")		
Ribbon Size	Length	Max 100m	
	Width	110mm +/- 0.5mm (4.33" +/- 0.002)	
	Wind Direction	Face Out	
FONT/SYMBOLOGIES			
Standard Fonts	Bitmap Fonts	Alphanumerical and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)	
	Rasterized Fonts	CG Times, CG Triumvirate, CG Times Bold, CG Triumvirate Bold	
Barcode	1D Barcode	UPC-A/ UPC-E, EAN8/13, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR(NW-7), ITF, INDUSTRIAL 2of5, MATRIX 2of5, BOOKLAND, MSI, POSTNET, GS1 DATABAR (RSS)	
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)	
Compositte Symbols		EAN-13 Composite (CC-A/CC-B), EAN-8 Composite (CC-A/CC-B), UPC-A Composite (CC-A/CC-B), UPC-E Composite (CC-A/CC-B), GS1-128 Composite (CC-A/CC-B/CC-C), GS1 DataBar Composite (CC-A/CC-B), GS1 DataBar Truncated Composite (CC-A/CC-B), GS1 DataBar Stacked Composite (CC-A/CC-B), GS1 DataBar Stacked Omni-Directional Composite (CC-A/CC-B), GS1 DataBar Limited Composite (CC-A/CC-B), GS1 DataBar Expanded Composite (CC-A/CC-B), GS1 DataBar Expanded Stacked Composite (CC-A/CC-B)	
Print Direction		Character & Barcode: 0°, 90°, 180°, 270°	
COMMUNICATION INTERFACE			
Interface		USB (B Type) + RS-232C (D-SUB 9 Pin) Model, USB (B Type) + LAN (10BASE-T/100BASE-TX Auto Switching) Model, USB (B Type) + IEEE1284 Model	
Command		SBPL	
OPERATING CHARACTERISTICS			
Power Requirements	AC Adaptor	Input Voltage: AC100V ~ 240V +/- 10%, Rated Input Voltage: AC100V / AC240V, Output Voltage: 19V	
Consumption Voltage		At Peak: 50W, At Waiting: 2.5W	
Environment	Operating	4 ~ 38°C / 30 ~ 80% RH (without condensing)	
	Storage	-10 ~ 60°C / 15 ~ 85% RH (without condensing)	
Dimension		(WxDxH): 179 x 238 x 173mm (7.05" x 9.37" x 6.81") Except protrusion part	
Weight		DT: 1.7kg (3.5 lbs) TT: 1.9kg (4.2 lbs)	
OPTIONS		Cutter, Dispenser, RTC, Keypad, Unwinder, SATO Label Gallery™	
MISCELLANEOUS			
Regulatory Approvals		USA/CANADA: UL60950-1 (2001), CSA22.2 No. 60950-1-03, EUROPE: EN60950-1, CE CHINA: CCC (GB4943-2001)	
Antibacterial Finishing		Resin of the enclosure/control panel includes an antibacterial substance. This substance is tested according to JIS Z 2801. JIS stands for Japanese Industrial Standard; JIS Z 2801 was designed to quantitatively measure the ability of an antimicrobial surface to kill or inhibit the growth of microorganisms.	

For more information about SATO in the region, visit www.satoasiapacific.com or simply scan the QR code below:

