



MB4i

MOBILITY AND PORTABILITY

FEATURES

- // Small Footprint
- // Lightweight
- // Compatible with PDA
- // 2-Colour Printing
- // Wireless Connectivity

APPLICATIONS

- // Logistics
- // Warehouse
- // Retail
- // Mobile Printing
- // Field Service

TECHNICAL INFORMATION

MB400i / MB410i

PRINTING SPECIFICATION		MB400i	MB410i
Printing Method		Direct Thermal	
Print Resolution, dots/mm (dpi)		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max. Print Area	Width, mm (inch)	104mm (4.09")	
	Length, mm (inch)	297mm (11.7")	
Print Speed, mm/sec (ips)		Up to 103mm/sec (4ips)	
CPU		32 bit RISC	

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Sensor Type		I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)	
Media Type		Roll die cut labels, Plain paper face stock, Linerless labels, Synthetics and Continuous stock	
Media Thickness		0.064 – 0.19mm (0.0025" – 0.0075")	
Label Shape	Diameter	Max. outside diameter: Ø 67mm (2.64"), Core diameter: Ø 19mm (0.75") or Ø 25.4mm (1")	
	Wind Direction	Face-out	
Label Size	Continuous	Width	50 – 111mm (1.97" – 4.37")
		Length	25 – 297mm (0.98" – 11.7")
	Tear-Off	Width	50 – 111mm (1.97" – 4.37")
		Length	25 – 297mm (0.98" – 11.7")
	Dispenser	Width	50 – 111mm (1.97" – 4.37")
		Length	25 – 182mm (0.98" – 7.17")

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumeric and Symbol: XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

COMMUNICATION INTERFACE		
Command Set		Either SBPL 4.0 or MB400 compatible command set
Interface	Standard Model	RS-232C, USB, Infrared (IrDA Ver.1.2, BHT protocol, IrCOMM, IrOBEX)
	Bluetooth Model	Bluetooth, RS-232C, USB, Infrared (IrDA Ver.1.2, BHT Protocol, IrCOMM, IrOBEX)
	Wireless LAN Model	Wireless LAN 802.11b/g, RS-232C, USB, Infrared (IrDA Ver.1.2, Standard Protocol, BHT Protocol, IrCOMM, IrOBEX)

OPERATING CHARACTERISTICS		
Power Requirements		Input voltage AC100-240V (auto switching)/90W Input voltage printer: 19V/4,9A
Dimensions		Standard Version: (W x D x H): 170 x 76 x 134mm (9.7" x 3.0" x 5.3") Industrial Version: (W x D x H): 202 x 99 x 165mm (8.0" x 3.9" x 6.5")
Weight		Standard Version: 750g (with battery installed) Industrial Version: 910g (with battery installed)
Environment	Operating	-15 – 50°C (Only the Wireless LAN Model : 0 – 50°C)
	Storage	-25 – 60°C (without condensation)

MISCELLANEOUS	
Certifications	FCC, UL, CSA, CCC, CE, ROHS compliant, Bluetooth® certified
Power Management	Auto power saving, power is automatically off with operation interval longer than 5 minutes (default) which may be set by command to other length of time. Auto power-off is disabled by default for Wireless LAN, Bluetooth configuration
Self Diagnostics	Print head check / Battery check / Paper end detection / Cover open detection, Test print: status identified with different colour signals
Regulatory Approvals	CSA (CSA22.2 NO.60950-1-03), CCC (GB4943-2001), SS337:2001, MIC, EK (AC adaptor only), FCC15B Class B, GB9254-1998, GB17625.1 (2003), EN55022, EN55024, FCC15C, GB4943, GB9254, GB17625.1, R&TTE (EN300 328 V1.4:2003-04), (EN301 489 V1.4.1:2002-08), IDATSSSS, FCC47 CFR2.1093, Bluetooth logo certified

OPTIONS	
Accessories	Battery Charger, AC Adaptor, Linerless Kit (Standard), Shoulder Belt, Battery Charger, Water Protective Case, Belt Bag, DC/DC Converter, SATO Label Gallery™

SATO makes no guarantee that the above features are available in all models, and specifications are liable to change, without notice. Version 09/10. * Measurements are approximate values.



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech


PRINTRONIX

symbol®


Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers




Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)



All Brands
Technical Service