WELL24™ Day A19 E26 Dimmable

Yuji Lighting $^{\text{\tiny{\$}}}$ Well24 $^{\text{\tiny{TM}}}$ Day LED lamps provide optimal lighting solutions for all spaces which promoting daytime focus and productivity. Designed with Yuji Wellness technology, lamps emit a biological wellness spectrum, reducing the damage of the biological clock, allowing people to become more focused, whilst retaining a beautiful, soft white light quality. They are excellent for task, office, studio, manufactory etc. lighting.



Features













- Light recipe for energizing effect
- Film grade flicker free at 240 FPS shooting
- 3-year warranty

- Smooth dimming down to 5%
- Even light distribution
- Classic Edison bulb design

Specification

| Part Number | Power | CRI | Beam Angle | Color-Temp | Luminous Flux | ON/OFF | Lifetime |
|-------------|-------|-----|---------------|------------|------------------|---------|----------|
| L3210105.40 | 11W | 90+ | 200° | 4000K | 1100lm | 100,000 | 25,000hr |
| L3210105.50 | | | | 5000K | | | |

WELL24™ Day A19 Dimmable

| General Information | | | |
|---------------------|-------------------|----------------------|----------------|
| Cap base: | E26 | Nominal lifetime: | 25000 h |
| EU RoHS compliant: | Yes | Switching cycle: | 100000 X |
| Diameters: | 2.36 inch / 60 mm | Net weight per lamp: | 3.35 oz / 95 g |
| Height: | 4.61 inch /117 mm | | |

| Technical data—Photometrical | | | | |
|---------------------------------------|--------------------------------|------------------------|-----------------|--|
| Melanopic Ratio: | 0.92 @ 4000 K 1.03 @ 5000 K | Color-Temp: | 4000 K / 5000 K | |
| Melanopic Daylight Efficacy Ratio: | 0.79 @ 4000 K 0.93 @ 5000 K | Initial luminous flux: | 1100 lm | |
| Photobiological safety: | Exempt group | Color consistency: | SDCM<6 | |
| Color rendering index: | 90+ | Beam angle: | 200° | |

| Technical data—Electrical | | | | |
|---------------------------|--------|----------------------|--------|--|
| Power: | 11 W | Nominal voltage: | 120 V | |
| Power factor: | ≥ 0.98 | Input frequency: | 60 Hz | |
| Lamp current: | 95 mA | Starting time: | <0.5 s | |
| Dimmable: | Yes | Warm-up time (60 %): | <0.5 s | |

