

# LED Linear High Bay

## BUYER'S GUIDE





## LED Linear High Bay Specifications

<b>Size</b>	<b>1X2'</b> (23.82 x 12.6 x 3.78")	<b>1X4'</b> 45.87 x 12.6 x 3.78")
<b>SKU</b>	<b>LWHB-1x2-110W-W5000K</b>	<b>LWHB-1x4-225W-W5000K</b>
<b>Light Output</b>	<b>14,300</b>	<b>29,250</b>
<b>Watt</b>	<b>110</b>	<b>225</b>
<b>Input Voltage</b>	<b>120-277VAC</b>	<b>120-277VAC</b>
<b>Lumens/W</b>	<b>130</b>	<b>130</b>
<b>Color Temp</b>	<b>5000K</b>	<b>5000K</b>
<b>Warranty</b>	<b>5 years</b>	<b>5 years</b>
<b>CRI</b>	<b>&gt; 80</b>	<b>&gt; 80</b>
<b>Power Factor</b>	<b>&gt; 0.9</b>	<b>&gt; 0.9</b>
<b>Beam Angle</b>	<b>120°</b>	<b>120°</b>
<b>Dimming Type</b>	<b>0-10V VDC supported</b>	<b>0-10V VDC supported</b>

1. UL & DLC FCC listed
2. High quality isolated driver; 0-10V dimming; Flicker free
3. PF > 0.90, driver efficiency > 87%; THD < 20%
4. Installation: pendant, chain mounting
5. Suitable for dry/damp location
6. Designed for warehouses, gymnasiums, and industrial spaces

**New York State Certified**  
Service-Disabled Veteran-Owned Business