LED WAVES

BUYER'S GUIDE

Adjustable MR16 Spotlights Suspended from Your Ceiling
Satin Nickel Finish Fixtures and Accessories

MONO-POINT *Fixtures*

An all-metal finish gives these fixtures an effortlessly sleek, modern look. The direction of each spotlight can be manually adjusted. Select fixtures available with light-diffusing louver.

OMEGA

ALPHA

ZETA

OMEGA Louver

EPSILON Louver

PI Louver

CHI-ZIGGURAT

EPSILON

PI

© 2017 LED WAVES, INC ALL RIGHTS RESERVED. V4-04-17

LED WAVES

BUYER'S GUIDE

Adjustable MR16 Spotlights Suspended from Your Ceiling
Delta Frosted Glass/Satin Nickel Finish Fixtures and Accessories

MONO-POINT

Delta-Fixtures

Classic meets contemporary in these mod style fixtures. The direction of each spotlight can be manually adjusted. Available with light-diffusing louver.

***DELTA** Cobalt*

***DELTA** Frosted*

***DELTA** Cognac*

***DELTA** Cobalt Louver*

***DELTA** Frosted Louver*

***DELTA** Cognac Louver*

© 2017 LED WAVES, INC ALL RIGHTS RESERVED. V4-04-17

LED WAVES

BUYER'S GUIDE

Adjustable MR16 Spotlights Suspended from Your Ceiling
Satin Nickel Finish Fixtures with Frosted Glass Shades

MONO-POINT

Chi-Fixtures

These satin nickel fixtures feature a semi-opaque shade to help obscure the LED bulb.
The direction of each spotlight can be manually adjusted.

CHI-CONE Frosted

CHI-CONE Blue

CHI-CONE Green

CHI-DECO Frosted

CHI-DECO Blue

CHI-DECO Cognac

CHI-DECO Green

CHI-DECO Burgundy

NEO-CONE Frosted

NEO-CONE Blue

NEO-CONE Cognac

NEO-CONE Yellow

NEO-CONE Red

CHI-ZIGGURAT Frosted

CHI-ZIGGURAT Blue

CHI-ZIGGURAT Green

© 2017 LED WAVES, INC ALL RIGHTS RESERVED. V4-04-17

LED WAVES

BUYER'S GUIDE

MR16 Pendant Light Fixtures Suspended from Your Ceiling
Satin Nickel Finish Fixtures with Frosted Glass Shades

MONO-POINT

Glass Suspension

These pendant light fixtures feature glass shades in a variety of colors and styles. Each fixture comes with a set of adjustable 36-inch suspension cables that connect to the power supply in the ceiling.

***LAMBDA** Frosted*

***LAMBDA** Cobalt*

***LAMBDA** Cognac*

***LAMBDA** Green*

***LAMBDA** Yellow*

***LAMBDA** Red*

***PYRAMID** Frosted*

***PYRAMID** Blue*

***PYRAMID** Salmon*

© 2017 LED WAVES, INC ALL RIGHTS RESERVED. V4-04-17

LED WAVES

BUYER'S GUIDE
Bulbs
About the Mono-Point MR16 LED light bulb

MONO-POINT

Included with each Mono-Point fixture is a highly efficient Athens LED MR16.

This Energy Star rated bulb features 8 Nichia brand LEDs to minimize scalloping and deliver a uniquely pleasing quality of light. Each bulb is an 8-Watt equivalent to a 50-Watt halogen MR16.

Bulbs are available in three color temperatures:
- 2700K (Very Warm White)
- 3000K (Warm White)
- 4000K (Neutral White)

Choose from two beam spreads:
- 22 degrees (Narrow)
- 40 degrees (Wide flood)

ATHENS
2,700K
22⁰



ATHENS
3,000K
22⁰



ATHENS
4,000K
22⁰



ATHENS
2,700K
40⁰



ATHENS
3,000K
40⁰



ATHENS
4,000K
40⁰



© 2017 LED WAVES, INC ALL RIGHTS RESERVED. V4-04-17

LED WAVES

BUYER'S GUIDE
Easy as 1, 2, 3

MONO-POINT

Step-1 Fixtures & Bulbs

The easiest and most fun part is selecting the quantity and style of bulbs and fixtures for your Mono-Point lighting setup.

Choose from our wide selection of adjustable spotlight and pendant light fixtures. Identify the beam angle and color temperature of MR16 bulbs you need. (See previous pages for fixtures and bulb specifications).

Step-2 Power Supply

Each fixture comes with a dedicated 12 volt LED driver. This sits above the ceiling and connects to your building's line volt power (120VAC) in the ceiling.

DIMMABLE or NOT DIMMABLE:

Choose from dimmable or non-dimming power supply options. Dimmable power supplies are compatible with standard incandescent (AKA leading edge, or TRIAC) Forward Phase Control dimmers.

Step-3 Installation

Mechanical installation is a snap: Simply feed the power supply to the fixture. Each fixture includes canopy screws to tighten the fixture (orpendant cables) flush against the ceiling.

Make sure to turn the power OFF at the circuit breaker before attempting electrical installation. Connect the Mono-Point fixture to the LED driver via the attacked Quick Connect ends. Connect the driver to your building's line voltage using wire nuts (available form any hardware store).

© 2017 LED WAVES, INC ALL RIGHTS RESERVED. V4-04-17