



SMART LED T8 TUBES

BALLAST COMPATIBLE LED TUBE

THE SMART LED T8 TUBE IS A LONG-LASTING, ENERGY-EFFICIENT ALTERNATIVE TO THE 8-FOOT FLUORESCENT LIGHTS OFTEN INSTALLED IN OFFICES, HALLWAYS, CLASSROOMS, AND STORAGE OR MANUFACTURING FACILITIES.



SMART T8 ELECTRONIC BALLAST COMPATIBLE LED TUBE (4FT)

LIGHT OUTPUT: 2,035 lumens
WATTAGE: 18 watts maximum
EFFICACY: 113 lumens per watt
COLOR TEMPERATURE: Neutral White 4000K
BEAM ANGLE: Approx. 120°
LAMP HOLDER: G13 (both shunted & non-shunted sockets would work)
VOLTAGE: 100-277VAC 50/60Hz
LIFE SPAN: 50,000 hours
DIMENSIONS: LED tube: 47.24" (1200mm) x 1.0" (26mm)
PROTECTION RATING: UL listed, DLC

FEATURES

- ▶ 45 Watt / 4,500 lumen replacement for 8-foot (96-inch) single-pin fluorescent tubes
- ▶ Plug & Play; no need to bypass or remove existing electronic ballast. (Magnetic ballast MUST BE removed before installing SMART T8 Tube. Using SMART T8 Tube with magnetic ballast will void warranty. Direct connection is recommended for optimal efficiency)
- ▶ UL listed
- ▶ Instant-on, without the warm-up time, noise, or flicker of fluorescent lighting
- ▶ Backed by LED Waves' 5 year warranty
- ▶ May be eligible for rebates, tax exemptions, and other rewards



SMART T8 FA8 ELECTRONIC BALLAST COMPATIBLE LED TUBE (8FT)

LIGHT OUTPUT: 4,500 lumens
WATTAGE: 45 watts maximum
EFFICACY: 100 lumens per watt
COLOR TEMPERATURE: Cool White 5000K
BEAM ANGLE: Approx. 120°
LAMP HOLDER: FA8 (single pin)
VOLTAGE: 100-277VAC 50/60Hz
BALLAST COMPATIBILITY: Compatible with electronic fluorescent ballast (Magnetic ballast MUST BE removed before installing SMART T8 Tube. Using SMART T8 Tube with magnetic ballast will void warranty. Direct connection is recommended for optimal efficiency.)
LIFE SPAN: 50,000 hours
PROTECTION RATING: UL listed