

### Eigenschaften

- ❖ **Hohe Effizienz:** Die fortschrittliche 3-Busbar-Technologie und hochwertige monokristalline A-Grade Solarzellen sorgen für maximale Leistung.
- ❖ **Verbesserte Haltbarkeit:** Dank des PCB-Backsheets und der ETFE-Frontabdeckung ist das Panel hervorragend vor verschiedensten Umwelteinflüssen, wie Hitze und Salzwasser geschützt und ist weniger anfällig für Blasenbildung.
- ❖ **Robust und flexibel:** Das semiflexible Design ermöglicht eine Biegung von bis zu 18 Grad und ist auch bei vollflächiger Verklebung noch begehbar.
- ❖ **Einfache Installation:** -Das Panel wird mit vormontierten Solarkabeln und MC4-Steckern geliefert und kann leicht verklebt oder mit den Ringösen montiert werden.
- ❖ **Zuverlässige Qualität:** Hergestellt aus hochwertigen Materialien und gemäß den höchsten Qualitätsstandards von Offgridtec für eine langfristige, zuverlässige Leistung.



### Anwendung:


- ❖ im Marine-Bereich
- ❖ auf Wohnmobil, Bus und anderen Fahrzeugen
- ❖ gerundete Blechdächer
- ❖ zur Aufhängung z.B. beim Zelten


### Offgridtec PCB-ETFE 100W 39V semiflexibles Solarpanel

Artikelnummer	3-01-010835	NOCT	45+/-2°C
EAN	4250983255287	Temp.koeffizient Spannung	-0.36%/°C
Hersteller-Teilenummer	010835	Temp.koeffizient Strom	+0.07%/°C
Leistung (Pmax)	100W	Temp.koeffizient Leistung	-0.38%/°C
Systemspannung	24V	Betriebstemperatur	-40 to+85°C
Modulspannung (Vmp)	39,6V	Biessamkeit	max. 18 Grad (längsseitig)
max. Strom (Imp)	2,53A	Anschlussbox (IP)	IP65 / IP67
Leerlaufspannung (Voc)	46,61V	Größe Anschlusskabel	4mm
Kurzschlussstrom (Isc)	2,73A	Kabellänge	0,8m
max. Systemspannung (V)	200V/DC	Abmessungen	845 x 680 x 3 mm
Toleranz	±3 %	Gewicht	3,8kg
Zelltyp	monokristallin	Ösen	4 Ringösen
Zellwirkungsgrad	>21 %		
Zellgröße	158.75 x 39.69 mm		
Zellen pro Modul	72 (4 x 18)		
installierte Dioden	2x IOSQO50 Bypass Diode		



Über uns  
Offgridtec GmbH  
Im Gewerbepark 11  
84307 Eggenfelden

Kontakt  
 +49 8721 91994-00  
 info@offgridtec.com  
 www.offgridtec.com



### Characteristics

- ❖ **High Efficiency:** Utilizes advanced 3-busbar technology and A-grade monocrystalline solar cells for maximum power output and efficiency.
- ❖ **Enhanced Durability:** The PCB back sheet provides better heat tolerance compared to TPT modules, reducing the risk of bubble formation due to poor adhesion. The ETFE front cover offers excellent protection against environmental factors and is resistant to saltwater.
- ❖ **Solid and flexible:** The semiflexible design allows bending up to 18 degrees and remains slip-resistant even when fully adhered.
- ❖ **Easy Installation:** Comes with pre-wired MC4 connectors and can be easily adhered or mounted using the ring holes.
- ❖ **Reliable Performance:** Manufactured with premium-grade materials and built to the highest quality standards by Offgridtec, ensuring long-term, reliable performance.



### Applications

- ❖ marine applications
- ❖ on motorhomes, buses and other vehicles
- ❖ on curved metal roofs
- ❖ for camping and other outdoor activities

### Offgridtec PCB-ETFE 100W 39V semiflexible solarpanel

Article number	3-01-010835	NOCT	45+/-2°C
EAN	4250983255287	voltage temperature coefficient	-0.36%/°C
Manufacturer part number	010835	current temperature coefficient	+0.07%/°C
max. output	100W	power temperature coefficient	-0.38%/°C
system voltage	24V	operating temperature	-40 to+85°C
module voltage (Vmp)	39,6V	bendability	max. 18 degrees
max. current (Imp)	2,53A	junction box (IP)	IP65 / IP67
open circuit voltage (Voc)	46,61V	size connection cable	4mm
short circuit current (Isc)	2,73A	cable length	0,8m
max. system voltage	200V/DC	module size	845 x 680 x 3 mm
power tolerance	±3 %	weight	3,8kg
cell type	monocrystalline	eyelets	4 ring eyes
cell conversion efficiency	>21%		
cells size	158.75 x 39.69 mm		
cells per module	72 (4 x 18)		
diodes installed	2x IOSQO50 Bypass Diode		



About us  
Offgridtec GmbH  
Im Gewerbepark 11  
84307 Eggenfelden

Contact  
+49 8721 91994-00  
info@offgridtec.com  
www.offgridtec.com

