

AT388

Foldable RFID / Barcode Bluetooth Reader

High performance with Sleek design

- UHF EPC Gen2, ISO / IEC 18000-6C
- 1D & 2D Barcode Scanning
- Compatible with Windows, Android & iOS

Diversity in Connectivity

- BT V2.1+EDR / BLE V4.1

Unique & Rugged

- Ergonomic Design
- Foldable Antenna for your usage
- Dropspec 1.5m(5ft)
- IP65



Multi
Functional



Light &
Compact



Rugged



Foldable
Antenna



Elegant
Design



www.atid1.com
inquiry@atid1.com
+82-2-544-1436

Specification

PERFORMANCE	
Processor	ARM7 Core
Supported Platforms	Windows, Android, iOS (BLE Only)
Internal Storage	1MByte Flash Memory
PHYSICAL CHARACTERISTICS	
Dimensions (W x L x H)	50 x 164 x 30 (54) mm
Weight	210g (Reader Only, without Battery)
Power	3,200mAh Lithium-Ion Battery (Rechargeable, 18650)
Display	1.3 inch OLED Display
USB Interface	1 USB Port / Micro USB
Notification	LED Indicator, Buzzer, Vibrator
DATA COLLECTION	
Protocol	EPC GEN2, ISO/IEC 18000-6C
Reading Range	~ 6m (Depending on environment and tag type)
Writing Range	~ 0.5m
RFID (UHF)	RF Output 1W (Max)
Frequency Range	US/FCC : 902MHz ~ 928MHz EU/CE : 865MHz ~ 868MHz KR/KC : 917MHz ~ 921MHz JP/TELEC : 916MHz ~ 921MHz (1W) 916MHz ~ 924MHz (0.25W / Optional)
Antenna	Circular Antenna / 1dBi
Barcode	2D Engine (Support to read 1D & 2D Barcode)

COMMUNICATION	
Bluetooth	BT V2.1 + EDR / BLE V4.1
USER ENVIRONMENT	
Operating Temp	-20°C to 50°C
Storage Temp	-30°C to 70°C
Charging Temp	0°C to 45°C
Humidity	5 ~ 95% (non-condensing, +25°C)
Drop Spec	1.5m
Sealing	IP65

* All Features and specifications described are subject to change without notice.



Accessories



Handstrap

USB Cable

