

# Wristband Silicone POWER



Specifications	
Dimensions	• 237 x 19 mm
Material (Band / Inlay)	Silicone
Protection Class	IP68
Printable area	32 x 12 mm

## \*STANDARD COLORS

PANTONE 361 C	PANTONE 102 C	PANTONE 021 C	PANTONE 485 C	PANTONE 1915 C	PANTONE 2592 C
PANTONE 304 C	PANTONE 284 C	PANTONE 286 C	PANTONE BLACK C	PANTONE COOL GREY 11 C	WHITE

\*MOQ for unique colors - 1000pcs



Logo produced through screen printing



Logo engraving with color fill



Logo engraving without color fill

## APPLICATIONS

- Fitness and Wellness areas
- Swimming pools
- Hotels
- Healthcare facilities

## PERSONALIZATION

- Logo printing (silkscreen)
- Logo engraving (optionally with one-/two-color filling)
- Serial number printing/ engraving
- Chip Encoding

## CHIPOPTIONS

### LF (125 kHz ICs)

- EM 4200
- Atmel Temic 5577
- NXP Hitag 1
- NXP Hitag 2
- NXP Hitag S2048

### HF (13,56 MHz ICs)

- NXP MIFARE Ultralight® EV1
- NXP MIFARE® Classic 1K EV1 4byte / 7 Byte
- NXP MIFARE® DESFire® EV1 2K/4K/8K
- NXP MIFARE® DESFire® EV2 2K/4K/8K
- NXP MIFARE® DESFire® EV3 2K/4K/8K
- NXP I-Code SLI
- NXP I-Code SLI-X
- LEGIC MIM256
- LEGIC MIM1024
- Tag-it HF-I
- NXP NTAG213 / 215 / 216
- IDT M1K (Fudan)

More Chiptypes on request!