

Wristband Silicone SMART



Specifications	
Dimensions	<ul style="list-style-type: none"> • 55mm (Children) • 65mm (Women) • 74mm (Men)
Material	Silicone
Protection class	IP68

*STANDARD COLORS

PANTONE 361 C	PANTONE 102 C	PANTONE 021 C	PANTONE 485 C	PANTONE 1915 C	PANTONE 2592 C
PANTONE 304 C	PANTONE 284 C	PANTONE 286 C	PANTONE BLACK C	PANTONE COOL GREY 11 C	WHITE

*MOQ for unique colors - 1000pcs



Logo produced through screen printing



Logo engraving with color fill



Logo engraving without color fill

APPLICATIONS

- Fitness and Wellness areas
- Swimming pools
- Hotels
- Healthcare facilities

PERSONALIZATION

- Logo printing (silkscreen)
- Logo engraving (optionally with one-/two-color filling)
- Serial number printing/engraving
- Chip Encoding
- Screen printing

CHIPOPTIONS

LF (125 kHz ICs)

- EM 4200
- Atmel Temic 5577
- NXP Hitag 1
- NXP Hitag 2
- NXP Hitag S2048

HF (13,56 MHz ICs)

- NXP MIFARE Ultralight® EV1
- NXP MIFARE® Classic 4K EV1 4Byte / 7 Byte
- NXP MIFARE® DESFire® EV1 2K/4K/8K
- NXP MIFARE® DESFire® EV2 2K/4K/8K
- NXP MIFARE® DESFire® EV3 2K/4K/8K
- NXP I-Code SLI
- NXP I-Code SLI-X
- LEGIC MIM256
- LEGIC MIM1024
- Tag-it HF-I
- NXP NTAG213 / 215 / 216
- IDT M1K (Fudan)

More Chiptypes on request!