

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

INSTALLATION GUIDE



175507 60/40 Rear Bench

TOYOTA TACOMA (2016-2022)



BILL OF MATERIALS

ITEM	QUANTITY
60 Portion Back Cover	1
60 Portion Bottom Cover	1
40 Portion Back Cover	1
40 Portion Bottom Cover	1
Headrest Covers	3

Seat Backs & Bottoms have tags signifying Driver or Passenger.

Ensure airbag patch (same side as the TigerTough tag) goes on the outside edge of the seat.

Watch the installation video at ttcovers.com/175507video

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
Drip dry or machine tumble dry on a no heat cycle.
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.




*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

Install Seat Bottom Cover

Remove headrests. Start with the 40 portion back. Flip seat back forward by pulling the strap at the top of the seat. Turn cover 3/4 of the way inside out and slide over seat back. Begin working the cover down the seat back.



Work headrest holes through the cover. Press cover underneath the plastic trim for a clean, finished look.



Flip the seat bottom up. Work the cover the rest of the way down the seat back.



Fold the seat back forward so that the velcro can be fastened together behind the seat. The tighter you pull the velcro, the better the cover will fit!



Undo all velcro flaps on the seat bottom. Tip seat bottom up. Arrange the cover as shown.



Fasten the velcro together as shown in the picture.

Repeat these steps on the other portion of the seat.



Insert headrests and pull headrest covers on.

Fasten the velcro underneath.



