

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

PART:	32507
PRODUCT:	AIR RIDE PASSENGER'S SEAT WITH INSIDE ARMREST COVER
FITMENT DETAILS:	FREIGHTLINER CASCADIA ISRI
PIECES:	(1) BACK (1) BOTTOM (1) ARMREST



*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
Drip dry or machine tumble dry on a no heat cycle.
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Seat Cover

SEAT DOES NOT NEED TO BE REMOVED TO INSTALL COVER.

Turn seat back cover partly inside out. Slide over the top of the seat. Make sure the armrest hole is on the correct side.




From behind the seat, pull the tabs tight and secure to velcro on the back of the seat cover.

Work the cover all of the way down the seat back. Un-do the velcro flap below the armrest so that you can pull it all of the way down.




Place the seat bottom cover over the seat bottom with the flaps at the back. Push the flaps in between the seat back and seat bottom.

Push the velcro flaps in between the seat back and bottom.





Drop the string (shown in red) between the plastic trim and the seat cushion on both sides.

Fasten the velcro tab below the armrest.



From behind the seat, pull the strings tight underneath and secure with the StringLock. (see next page)

THE STRINGLOCK




1

Run one string through the channel on the end of the StringLock.



2

Pull the string tight, pulling the StringLock towards one edge of the seat. Press the string into the clamp, locking it in place.




3

Run the second string through the StringLock just like the other one.



4

Pull the loose end of the second string until everything is tight and lock it into place as well.



Watch the video
ttcovers.com/stringlock

Install Seat Cover

Install armrest cover.



Fasten the armrest cover at the back.

You'll know you have it on the right way if the top flap is over the bottom flap.



FINISHED!

CALL US AT 507.246.3545. FOR INSTALLATION ASSISTANCE