

It's not rocket science,  
but following these  
instructions will make  
installing your seat covers  
a lot easier.

We promise.

<b>PART:</b>	<b>E82202</b>
<b>PRODUCT:</b>	<b>KUBOTA U55-5 SEAT COVER</b>
<b>PIECES:</b>	(1) SEAT BACK COVER (1) SEAT BOTTOM COVER



*Basically, you break it, we buy it.  
Seriously.*

**Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.**

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

### General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.  
Drip dry or machine tumble dry on a no heat cycle.  
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

# Install Seat Cover

Pull seat back cover over with the 3 velcro flaps at the front.



1

Place the seat bottom cover over the seat bottom with the velcro tabs towards the back.



5

Work cover around the adjustment lever on the side of the seat.



2

Push the velcro tabs through the gap between the seat back and seat bottom.



6

Push the 3 velcro flaps through the gap between the seat back and bottom.



3

Pull tabs tight and secure to the velcro on the back of the other tabs.



7

Pull the flaps tight and secure to the velcro.



4



Mission accomplished.