It's not rocket science, but following these instructions will make installing your seat covers installing your seat covers a lot easier.

We promise.

PART: | E82209

PRODUCT: CAT D SERIES EXCAVATOR

SEAT COVER

PIECES: (1) SEAT BACK (1) SEAT BOTTOM (1) HEADREST



Basically, you break it, we buy it. Seriously.

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

General care instructions:

- 1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
- 2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
 - Drip dry or machine tumble dry on a no heat cycle.
 - Straps should be coiled and secured with rubber bands for machine washing and drying.
- 3. Soil may be removed with spray cleaner or detergent and water.
- 4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
- 5. Do not use bleach.

Install Seat Back & Headrest

Undo velcro on the seat back. Slide cover over the seat back and headrest with the pocket on the back of the seat.





Push the velcro flaps between the seat back and seat bottom. Pull tight and secure at the back.

Work cover around the knob on the side of the seat. Fasten the velcro tab below the knob.





Fasten velcro flaps below the headrest to the velcro inside the seat cover.

Slide the cover between the lever and seat on the other side.





Put headrest cover on with the flap towards the front.

Secure flap to the velcro sewn on the inside of the headrest cover.

Install Seat Bottom Cover

Slide seat bottom cover on with the velcro flap towards the back.



Push velcro flap between the seat back and seat bottom.



[View from back of seat]

Pull tight and secure to velcro.



FINISHED.