

It's not rocket science,  
but following these  
instructions will make  
installing your seat covers  
a lot easier.

We promise.

**PART:** E82211  
**PRODUCT:** KOMATSU DOZER SEAT COVER

**PIECES:** (1) SEAT BACK COVER  
(1) SEAT BOTTOM COVER  
(1) HEADREST COVER

FOR INSTALL HELP, CALL 507.246.3545



*Basically, you break it, we buy it.  
Seriously.*

**Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.**

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

### General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.  
Drip dry or machine tumble dry on a no heat cycle.  
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

# Install Cover

Start with the seat back. Undo all the velcro tabs on the cover. Slide cover over the headrest.

The flaps at the bottom should be facing you.



[View from back of seat]

Pull tight and secure to the velcro at the back.

Work the cover the rest of the way down the seat back.



Fasten the tab beneath the headrest to the velcro on the inside of the cover.



Fit the cover around the switch, knob, and make sure it's behind the lever on the side of the seat.



Place the seat bottom cover over the seat bottom.

Tuck fabric around the plastic trim of the adjustment handle at the front.

Push the tabs in between the seat back and seat bottom.



Push flap in between the seat back and seat bottom.

Pull tight and secure velcro.

Pull headrest cover on with the long velcro flap towards the front.



Fasten the flap to the velcro on the inside of the back of the headrest cover.

**MISSION  
ACCOMPLISHED**

