

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

PART: E82214
PRODUCT: CAT SELECT D, E, AND F SERIES
EXCAVATOR SEAT COVER

PIECES: (1) SEAT BACK COVER
(1) SEAT BOTTOM COVER
(1) HEADREST COVER

FOR INSTALL HELP, CALL 507.246.3545



*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
Drip dry or machine tumble dry on a no heat cycle.
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Cover

Undo the velcro tabs on the seat cover.

Begin pulling the cover on with the pocket facing the back.



[View from back of seat]

Pull tight and secure to the velcro at the back.

Work the cover down the seat back. Pull around the gray knob on the side and tuck the seam in around it.



Fasten the tab beneath the headrest to the velcro on the inside of the cover.

Fasten tabs under the headrest to the velcro on the edge of the cover as show.



Place the seat bottom cover over the seat bottom.

Tuck fabric around the plastic trim of the adjustment handle at the front.

Push the tabs in between the seat back and seat bottom.



Push flap in between the seat back and seat bottom.

Pull tight and secure velcro.

MISSION ACCOMPLISHED

