

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

PART:	E82236
PRODUCT:	CAT NEXT-GEN MINI EXCAVATOR SEAT COVER
PIECES:	(1) SEAT BACK COVER (1) SEAT BOTTOM COVER



*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
Drip dry or machine tumble dry on a no heat cycle.
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Seat Cover

You do not need to remove the seat to install cover.

Turn seat back cover 1/2 way inside out. Slide over seat with the three velcro tabs at the front.



Pull tight and secure to the velcro on the back of the cover.

Unroll down the seat back. Tuck cover behind yellow lever.

Push tabs in between the seat back and bottom.



Pull tabs tight and secure to the velcro on the back of the cover.



Place seat bottom cover over seat bottom. Push tabs between the seat back and bottom.



FINISHED!