

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

PART:	E82238
PRODUCT:	KUBOTA U35-4, U48-4, U55-5, KX033-4, KX040-4 EXCAVATOR, ENCLOSED CAB SEAT COVER
PIECES:	(1) SEAT BOTTOM (1) SEAT BACK



Basically, you break it, we buy it.
Seriously.

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent. Drip dry or machine tumble dry on a no heat cycle. Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Seat Bottom Cover

SEAT DOES NOT NEED TO BE REMOVED FROM MACHINE

Turn seat back 3/4 of the way inside out and slide over the seat.



Push the flaps between the seat back and bottom.



Begin working it down the seat back. This one fits tight!



Pull tight and secure to the velcro at the back.



Make sure the adjustment lever comes through the hole in the cover.



Place seat bottom cover over the seat bottom. Push flap between the back and bottom.



Pull seat cover the rest of the way down.



Pull tight and secure to velcro.



CALL US AT 507.246.3545. FOR INSTALLATION ASSISTANCE