

It's not rocket science,  
but following these  
instructions will make  
installing your seat covers  
a lot easier.

We promise.

<b>PART:</b>	<b>E82239</b>
<b>PRODUCT:</b>	<b>KUBOTA U35-4, U48-4, U55-5, KX033-4, KX040-4 EXCAVATOR, OPEN CAB SEAT COVER</b>
<b>PIECES:</b>	<b>(1) SEAT BACK (1) SEAT BOTTOM</b>



Basically, you break it, we buy it.  
Seriously.

**Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.**

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

### General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent. Drip dry or machine tumble dry on a no heat cycle. Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

# Install Seat Bottom Cover

**SEAT DOES NOT NEED TO BE REMOVED FROM MACHINE**

Slide the seat back cover on with the velcro tabs facing the front.

Push tabs between the seat back and bottom.



Place seat bottom cover over seat bottom.

Push the flaps between the seat back and bottom.



Pull tabs tight and secure to the velcro behind the seat.



Pull tabs tight and secure to the velcro behind the seat.

