

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

PART:	E82248
PRODUCT:	CAT NEXT-GEN MINI EXCAVATOR SEAT COVER
PIECES:	(1) SEAT BACK COVER (1) SEAT BOTTOM COVER

LIFETIME WARRANTY

*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by an unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're suppose, we'll make it right.

Depending on what is more practical, we'll either repair or replace the damaged cover.

This warranty only applies to the original purchaser.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent. Drip dry or machine tumble dry on a no heat cycle. Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Seat Cover

Turn seat back cover halfway inside out. This will help it fit snug against the top of the seat.

Slide over the seat back with the hook-and-loop tabs towards the front.



Place seat bottom cover on the seat bottom. Push the tabs between the seat back and bottom.

Work the rest of the way down the seat back. Push the tabs between the seat back and bottom.



Run the flaps under the seat and through the gap made by the seat belt. Fasten tightly to the hook-and-loop at the back.

Pull tabs tight and fasten at the back.



Finished!