

INSTALLATION GUIDE



T62210 Tactical Driver's Seat Cover

Chevrolet Silverado 1500 (2019)

GMC Sierra 1500 (2019)



BILL OF MATERIALS

ITEM	QUANTITY
Driver Seat Back Cover	1
Driver Seat Bottom Cover	1
Seat Headrest Cover	1

Ensure airbag patch (same side as the TigerTough tag) goes on the outside edge of the seat.

Watch the installation video at ttcovers.com/t6210video

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
Drip dry or machine tumble dry on a no heat cycle.
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.



1 - Preparation



- 1.1 - Slide seat forward and raise to highest position, if possible.
- 1.2 - Lift headrest up by pressing the button on the side of the headrest and pulling up.
- 1.3 - Turn the trim pieces at the top of the seat back counter clockwise to loosen them.
- 1.4 - Use a small flat screwdriver to release the headrest retainer at the base of each headrest post by prying it up and forward at the same time. Instructions here: ttcovers.com/chevyheadrest
- 1.5 - Once both retainers are released, pull the headrest out of the seat back.

2 - Install Seat Back Cover



- 2.1 - Unhook both elastic straps from under the seat bottom to release the seat back flap.
- 2.2 - Lean seat back forward.
- 2.3 - Turn seat back cover 3/4 of the way inside out and pull over seat back.
- 2.4 - Line holes in cover up with headrest holes.
- 2.5 - Continue pulling the cover down over the seat, unrolling it as you go.
- 2.6 - Push factory seat back flap into space between seat back and seat bottom.
- 2.7 - Push front flap between seat back and seat bottom.
- 2.8 - Pull front flap as tight as possible and fasten to Velcro on seat back.

For assistance with installation, call us at 507.246.3545



3 - Install Seat Bottom Cover



Seat cover string between seat bottom and plastic trim, where back and bottom meet.



- ❑ 3.1 - Put cover over seat bottom.
- ❑ 3.2 - Tuck cover behind plastic trim around seat. The seams in the cover will line up with seat seams.
- ❑ 3.3 - Tuck outside string between seat bottom and trim, where the back and bottom meet. Inside string goes under seat bottom, in front of rear seat mount.
- ❑ 3.4 - Push top flap between seat back and seat bottom. Pull tight to line cover up with seat bottom.
- ❑ 3.5 - Pull strings tight.
- ❑ 3.6 - Tie a loop in one string. Run the other string through the loop, pull tight, and tie string back on itself. It is important to pull tight as this is what keeps your cover from shifting.
- ❑ 3.7 - Run front flaps over all seat adjustment levers, wires, and brackets.
- ❑ 3.8 - Pull front flaps as tight as possible and fasten to Velcro on top flap.
- ❑ 3.9 - Fasten long flap from seat back under seat bottom.

4 - Install Headrest Cover



- ❑ 4.1 - Put headrest back in seat by pressing it back into place.
- ❑ 4.2 - Pull cover over head rest with “loop” Velcro in front and “hook” Velcro in rear.
- ❑ 4.3 - Fasten Velcro tabs together under headrest.
- ❑ 4.4 - Tuck cover behind plastic trim around button.