

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

PART:	U192503
PRODUCT:	FRONT 60/40 SPLIT BENCH WITH HEADREST COVERS
FITMENT DETAILS:	POLARIS RANGER CREW XP 1000
PIECES:	(1) 40 PORTION BACK (1) 40 PORTION BOTTOM (1) 60 PORTION BACK (1) 60 PORTION BOTTOM (2) HEADREST COVERS

Seat Backs & Bottoms have tags signifying Driver or Passenger.

LIFETIME WARRANTY

*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by an unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

This warranty only applies to the original purchaser.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent. Drip dry or machine tumble dry on a no heat cycle. Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Seat Cover

page 1

Alright - let's go!

If your seats are dirty, now's your chance to clean them up before you cover them.



Fasten the upper and lower tabs tightly together at the back as shown.

Let's start with the driver's seat bottom.

Undo all of the tabs on the seat cover.



Next, pull the tabs on each side tight and secure.

Release the seat bottom with the tab at the back of the seat bottom.

Put the cover around that tab as shown.



Undo all of the tabs for the seat back, and place it over the seat back.

Work the cover over the front corners of the seat bottom.



There's one long tab on each side. Fasten them tightly together behind the seat.

Install Seat Cover

page 2

Pull the tab at the bottom of the front tight. Wrap it up and around the back to secure it.



Having the 'soft' side of the tab facing the back of the cab makes this easier, so it doesn't stick on the way down.

Reach up from the bottom and secure it to the two tabs you already secured behind the seat.

The passenger side seat back is a similar concept.

Undo all of the tabs. Place the cover over the seat back with the tag facing the door.



Next, wrap the tabs at the bottom of the seatback cover under the seat and secure behind it.

Pulling this tight is key to a great fit!

The long tabs on the left and right get secured to each other behind the seat.



Now for the seat bottom- place it on as shown with the long flaps towards the front.

Run this tab at the top down behind the seat.



Flip the seat upward.

Run the split flaps under the seat, and work the other flap through from the bottom.

Install Seat Cover

page 3

Pull everything tight and fasten together.



Pull the little tab on the side tight and secure it.



The headrest cover is the simplest piece! Just put it on and fasten the tabs underneath.

