

It's not rocket science,  
but following these  
instructions will make  
installing your seat covers  
a lot easier.

We promise.

PART:	U192507
PRODUCT:	60/40 SPLIT BENCH WITHOUT HEADREST COVERS
FITMENT DETAILS:	SIDE-BY-SIDE
PIECES:	(1) 40 PORTION BACK (1) 40 PORTION BOTTOM (1) 60 PORTION BACK (1) 60 PORTION BOTTOM

*Seat Backs & Bottoms have tags signifying Driver or Passenger.*

# LIFETIME WARRANTY

*Basically, you break it, we buy it.  
Seriously.*

**Your new seat covers are covered by an unconditional, no B.S. warranty.**

That means that if you manage to abuse them to a point that they can't perform like they're supposed to, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

This warranty only applies to the original purchaser.

## General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent. Drip dry or machine tumble dry on a no heat cycle. Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

# Install Seat Cover

page 1

Alright - let's go!

If your seats are dirty, now's your chance to clean them up before you cover them

Let's start with the bench back.

Undo all of the tabs on the seat cover and place it over the seat as shown.



Adjust the cover so everything lines up.

Locate the long tabs that run from side-to-side.

The long tabs at the top need to be dropped down behind the seat back.

\*NOTE: see how that seat belt is stuck behind the seat? Yours shouldn't be like that. We had taken the seat back off for design, and accidentally bolted it back over the seat belt. We didn't realize until the install guide was done. Oops!



This part is hard to show, but connect the long straps from side-to-side

Work those tabs down the seat back - try to keep them from catching on the felt backing!



And then fasten the straps from the top to the ones running side-to-side.

Reach up from underneath to work them the rest of the way down.



# Install Seat Cover

page 2

Next, wrap the tabs from the bottom up to connect to the straps running behind the seat from side-to-side.



Now for the smaller portion of the bench seat.

Undo all of the tabs. Hook the cover around this metal peg as shown, and then line it up on the rest of the seat.

And do this for all of them, all the way across. Make sure everything is good and snug - it's what will give your cover a great fit!



Like this.

Now for the larger portion of the bench bottom. Place the cover over top. Flip the bench up. Run the long flaps down the underside of the bench as shown.



Now, fasten the tabs on each edge.

Fasten the tabs top over bottom first.

Fasten those flaps at the back of the bench cover.



Then fasten the remaining two tabs on each side.

# Install Seat Cover

page 3

Now, headrests! Work the cover on as shown.

Tuck the tails up and fasten them inside the back of the headrest cover.



You're finished!

