



Hey there!

It's not rocket science, but following the instructions will make installing your seat covers a lot easier. We promise.

If you have any questions, comments, or issues, we're here to help! You can reach us at 507.246.3545 (call or text) or email orders@tigertough.com.

PART NUMBER

W1755010

PRODUCT TYPE

60/40 SEAT COVER

PIECES

(1) 60 PORTION BACK

(1) 60 PORTION BOTTOM

(1) 40 PORTION BACK

(1) 40 PORTION BOTTOM

(3) SEAT HEADREST

(1) ARMREST

VIDEO INSTRUCTIONS

case sensitive link

ttcovers.com/175510video





*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent. Drip dry or machine tumble dry on a no heat cycle. Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Seat Cover

page 1

Remove the outer headrests.



Make sure the seat release strap is coming through the slot in the cover.

Remove the middle headrest.



Work the cover down the seat back, making sure the armrest comes through the gap.

Starting with the 60 portion back: release the seatback by pulling the release tab.



Tuck the edges under the headrest holes for a clean, finished look.

Undo all tabs on the 60 portion seat back. Pull cover over the corners of the seat, and run it under the seat belt as shown.



The cover should line up with the carseat tether points on the back as shown.

Install Seat Cover

page 1

There's a flap below the armrest gap. Tuck it between the seat and the armrest.



Slide the armrest cover on as shown.

Pull it up and fasten it to the tab inside the cover.



Work the tab on the bottom of the amrest up through where the armrest hinges.

Fasten as shown.

Tip the seat forward to a 45 degree angle. Push the tabs between the seat back and bottom.



Tuck the edge under the plastic trim for a finished look.

Pull tight and secure at the back.



Flip the seat bottom up. Put the cover and work it down the seat bottom as shown.

Install Seat Cover

page 1

Fold the seat bottom down. Make sure the seat belt receiver is exposed by tucking the contour in the cover below it.



Fasten the little tab on the edge last.

Push the tabs between the seat back and bottom.

Holding the seat bottom slightly up makes this easier.



Put the outer headrests back on.

Slide the headrest covers on with the tab towards the front.

Pull the tabs tight, and secure to the seat bottom.



Fasten the tab to the inside of the headrest cover at the back.

The tighter you pull the tabs, the better the cover will fit.



Install Seat Cover

page 1

For the middle headrest-

The curved front part of the headrest fits in to the 'pocket'



Fasten as shown.

