

BRIGHTO ACRYLIC ROCK TOPCOAT

General Description	Brighto Acrylic Rock Topcoat is a high quality acrylic lacquer. It has superior color and gloss retention when exposed to harsh climate. It is lead and formaldehyde free.
Pack Size	0.90 Liter, 3.60 Liters, 18 Liters
Colour Range	See Brighto Acrylic Rock Top Coat shade card.
Film Properties	
Chemical Resistance	Resistant to mild chemical fume attack.
Composition (Nominal)	Pigment: Lightfast Pigments Binder: Acrylic Resin Solvent: Xylene
Volume Solids	38 ± 2% (nominal)
Density	1.09 ± 0.03; Theoretical
Non-volatile Matter Content	52 ± 2; Theoretical
VOC Contents	430 g/L ISO 11890-1
Film Thickness/Coat	Wet: 75 - 100 Micrometers Dry: 28 - 38 Micrometers
Drying Times	Depends on temperature, humidity, air movements and film thickness
Touch Dry	15 - 30 Minute
Recoat	1 Hour
Hard Dry	3 - 4 Hours
Theoretical Coverage	A guide to the theoretical coverage which can be achieved under normal conditions is 10-13 m ² /liter /coat.
Application	Brush, Roller, Spray
Thinner	Xylene / Brighto G.P Thinner.
Thinning	
Brush or Roller	5 - 10%
Conventional Spray	10 - 15%
Cleaning Up	Clean all equipment with Xylene / Brighto G.P Thinner.

**Surface Preparation
And Application**

If Brighto Acrylic Rock is to be applied on texture coatings, make sure surface is free from fungal growth or other surface contaminants. A coat of suitable undercoat / primer is recommended when applying on ferrous or Non-ferrous metal surfaces.

**Safety, Health and
Environmental
Information**

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use turpentine oil or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.