



# TECHNICAL DATA SHEET

## UNIVERSAL STAINERS

<b>General Description</b>	Universal Stainers are binder free concentrated pigment dispersion in aqueous solution. They have broad compatibility in water borne aqueous emulsion based on polymeric resins and solvent based alkyd enamels. Their high tinting strength ensures good results with minimum dosage.
<b>Key Features</b>	Easy to use. Both for interior and exterior application. Eco friendly. High Tint Weather Fast. Available in Nineteen different shades.
<b>Pack Size</b>	110 gram, 200 ml
<b>Colour Range</b>	Standard colour range of Brighto Universal Stainers
<b>Physical Characteristics</b>	Viscosity @ 25°C/77°F : 58-63 Krebs Unit Specific gravity @ 25°C/77°F : 1.1-1.7 PH : 8.75-9 Tint Strength : 100±0.05 Color Difference Delta E : ≤ 1
<b>Instructions For Use</b>	Shake the colorant or stainer well before use. Open the cap and simply add small quantities of this product to standard white paint until the correct shade of colour is achieved. Tinted paints should be mixed properly.
<b>Tools Checklist</b>	Paint Paddle, Rubber Gloves etc.
<b>Cleaning Up</b>	Clean all tools (brushes, paddle etc.) with clean water or Mineral Turpentine after use.
<b>Storage</b>	Store in a cool dry place but also protect from freezing.
<b>Safety, Health and Environmental Information</b>	Keep container tightly closed and upright to prevent leakage when not in use. Avoid contacts with eyes and skin. Wear gloves and goggles during working. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Close container tightly after each use. Keep out of reach of children.

*Any advice recommendations, information, assistance or service provided by Brighto Chemicals Pakistan Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.*