

BRIGHTO GRAFFIO

General Description	Brighto Graffio is a superior quality high build tinted trowel applied textured resin bonded plaster. It contains graded aggregates to produce a raked finish in various patterns. It is lead and formaldehyde free.
Pack Size	3.60 Liters, 18 Liters, 108 Liters
Colour Range	White / See Brighto Exterior Texture shade card
Film Properties Water Resistance	Will tolerate the levels of atmospheric humidity present in normal environments.
Composition (Nominal)	Pigment: Lightfast Pigments Binder: Acrylic copolymer Solvent: Water
Volume Solids	71 ± 2% (nominal)
Density	1.75 ± 0.03 Theoretical
Non-volatile Matter Content	82 ± 2; Theoretical
VOC Contents	<1 g/L ; ISO 11890-1
Film Thickness/Coat	Wet: 1500 - 2000 Micrometers Dry: 1000 - 1400 Micrometers
Drying Times	Depends on temperature, humidity, air movements and film thickness
Touch Dry Hard Dry	2 - 3 Hours 24 Hours
Theoretical Coverage	A guide to the theoretical coverage which can be achieved under normal conditions is 0.5 - 0.7 m ² /liter /coat.
Application	Special Trowel
Thinner	Water
Dilution	Maximum 10% (if Required)
Cleaning Up	Clean all equipment with clean water immediately after use.
Surface Preparation	New, bare, old or previously painted surface must be clean dry, free from wax and dust. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. Dust off with the help of cloth, Use the recommended application procedure for application. Stir thoroughly before use.

Recommended Paint System

Brighto Acrylic Primer / Brighto Texture Primer (Shade Close to Graffio)	1 - 2 Coats
Brighto Graffio	1 Coat

Safety, Health and Environmental Information

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.