

BRIGHTO HEAVY TEXTURE

General Description	Brighto Heavy Texture is a superior quality high build roller applied textured resin bonded plaster. It is suitable for exterior use on either new or previously painted walls that have been properly prepared. It contains graded aggregates to produce a raked finish in various patterns. High solid coating has the ability to hide hairline cracks. It is lead and formaldehyde free.
Pack Size	3.60 Liters, 18 Liters
Colour Range	White / Customize
Film Properties Water Resistance	Will tolerate the levels of atmospheric humidity present in normal environment.
Composition (Nominal)	Pigment: Lightfast Pigments Binder: Acrylic copolymer Solvent: Water
Volume Solids	72 ± 2% (nominal)
Density	1.70 ± 0.03 Theoretical
Non-volatile Matter Content	84 ± 2; Theoretical
Film Thickness/Coat	Wet: 750 - 1000 Micrometers Dry: 540 - 720 Micrometers
Drying Times	Depends on temperature, humidity, air movements and film thickness
Touch Dry Hard Dry	4 Hours 48 hours
Theoretical Coverage	A guide to the theoretical coverage which can be achieved under normal conditions is 1 – 1.5 m ² /liter /coat.
Application	Roller
Thinner	Water
Dilution	5 - 10% (if required)
Conventional Spray	Not Applicable
Cleaning Up	Clean all equipment with clean water immediately after use.

Surface Preparation

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the loose particles from surface through scraper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Apply **Brighto Acrylic primer**. Allow to dry. Apply **Brighto Heavy Texture**. Allow surface to dry completely. For color finish, apply any shade of Brighto exterior products.

Recommended Paint System

Brighto Acrylic Primer	1 - 2 Coats
Brighto Heavy Texture	1 Coat

Safety, Health and Environmental Information

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.