



# TECHINCAL DATA SHEET

## BRIGHTO HYBRID POWDER COATING

<b>General Description</b>	<b>Brighto Hybrid Power Coating</b> is designed & formulated to meet decorative appearance, gloss retention & color stability. It is well-suited to internal applications. It leaves a hard, smooth finish that has corrosion-resistant qualities. It provide smooth glossy looks to metal and build a good uniform cosmetic finish.
<b>Gloss @ 60 DEG</b>	97 +- 3
<b>Appearance</b>	Smooth Glossy
<b>Colour Range</b>	Standard colour range of Brighto Universal Stainers
<b>Recommended Film Thickness</b>	60 – 80 Microns
<b>Specific Gravity</b>	1.66
<b>Adhesion/Cross Cut</b>	No Peeling
<b>Tablet Flow</b>	6.0 cm/grams
<b>Curing Schedule</b>	10min/200°C or 15min/180°C + Metal Temperature
<b>Safety, Health and Environmental Information</b>	Keep container tightly closed and upright to prevent leakage when not in use. Avoid contacts with eyes and skin. Wear gloves and goggles during working. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Close container tightly after each use. Keep out of reach of children.

*Any advice recommendations, information, assistance or service provided by Brighto Chemicals Pakistan Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.*