

# ***BRIGHTO SAND TEXTURE***

<b>General Description</b>	<b>Brighto Sand Texture</b> is a superior quality high build roller applied textured resin bonded plaster. It is suitable for exterior use on either new or previously painted walls that have been properly prepared. It contains graded aggregates to produce a raked finish in various patterns. High solid coating has the ability to hide hairline cracks. It is formaldehyde free. It can be applied on plasters, concrete, masonry, wood, gypsum, and cement fiber panels.
<b>Pack Size</b>	3.60 Liters, 18 Liters
<b>Colour Range</b>	White / See Brighto Exterior Texture shade card
<b>Film Properties Water Resistance</b>	Will tolerate to the levels of atmospheric humidity present in normally environment.
<b>Composition (Nominal)</b>	Pigment: Inert Filler Binder: Acrylic Copolymer Solvent: Water
<b>Volume Solids</b>	White 56 ± 2% (nominal)
<b>Density</b>	1.65 ± 0.03; Theoretical
<b>Non-volatile Matter Content</b>	77 ± 2; Theoretical
<b>Film Thickness/Coat</b>	Wet: 260 - 800 Micrometers Dry: 160 - 500 Micrometers
<b>Drying Times</b>	Depends on temperature, humidity, air movements and film thickness
<b>Surface Dry Hard Dry</b>	2 - 3 Hours 12 Hours
<b>Theoretical Coverage</b>	A guide to the theoretical coverage which can be achieved under normal conditions is 0.8 - 2 m <sup>2</sup> /liter /coat.
<b>Application</b>	Roller
<b>Thinner</b>	Water
<b>Dilution</b>	5 - 10% (If Required)
<b>Conventional Spray</b>	Not applicable
<b>Cleaning Up</b>	Clean all equipment with clean water immediately after use.

## Surface Preparation

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of paris or white cement. Apply Brighto Acrylic primer. Allow to dry. Apply Brighto Sand Texture. Allow surface to dry completely. For color finish, apply any shade of Brighto exterior products.

## Recommended Paint System

Brighto Acrylic Primer	1 Coat
Brighto Sand Texture	1 Coat

## Safety, Health and Environmental Information

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

*Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.*