

# ***BRIGHTO SYNTHETIC UNDERCOAT***

<b>General Description</b>	<b>Brighto Synthetic Undercoat</b> is excellent quality alkyd based paint which gives maximum enamel hold out and provides smooth tough surface. It is highly recommended for use on all interior and exterior surfaces like wood, metal iron etc. It is free from lead and heavy metals.
<b>Pack Size</b>	0.90 Liter, 3.60 Liters, 18 Liters
<b>Colour Range</b>	White only
<b>Film Properties Water Resistance</b>	Resistant to mild chemical fume attack.
<b>Composition (Nominal)</b>	Pigment: Lightfast Pigments Binder: Alkyd Resin Solvent: Mineral Turpentine
<b>Volume Solids</b>	53 ± 2% (nominal)
<b>Density</b>	1.48 ± 0.03; Theoretical
<b>Non-volatile Matter Content</b>	75 ± 2; Theoretical
<b>Film Thickness/Coat</b>	Wet: 50 - 75 Micrometers Dry: 26 - 40 Micrometers
<b>Drying Times</b>	Depends on temperature, humidity, air movements and film thickness
<b>Touch Dry Recoat</b>	2 - 4 Hours 6 - 8 Hours
<b>Theoretical Coverage</b>	A guide to the theoretical coverage which can be achieved under normal conditions is 13 - 20 m <sup>2</sup> /liter /coat.
<b>Application</b>	Brush, Roller, Spray
<b>Thinner</b>	Mineral Turpentine / Brighto General Purpose (GP) Thinner
<b>Thinning Brush or Roller Conventional Spray</b>	5 - 10% 10 - 15%
<b>Cleaning Up</b>	Clean all equipment with mineral turpentine immediately after use.

**Surface Preparation**

New, bare, old or previously painted surface must be clean dry, free from wax and dust. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. Dust off with the help of cloth. Stir thoroughly before use.

**Recommended Paint System**

It is primer used as a basecoat for surface preparation of Brighto topcoats application.

**Safety, Health and Environmental Information**

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use turpentine oil or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

*Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.*