

BRIGHTO TEXO COMPOUND

General Description	Brighto Texo Compound is an intermediate textured coating specially formulated to give a textured surface by spray application. It is based on high quality acrylic copolymer emulsion containing fine quartz aggregate giving a textured tough decorative finish. It can be applied on plasters, concrete, masonry, wood, gypsum, and cement fiber panels.
Pack Size	3.60 Liters, 18 Liters
Colour Range	White / See Brighto Exterior Texture shade card
Film Properties Water Resistance	Will tolerate the levels of atmospheric humidity present in normal environment.
Composition (Nominal)	Pigment: Lightfast Pigments Binder: Acrylic Copolymer Solvent: Water
Volume Solids	61 ± 2% (nominal)
Density	1.74 ± 0.03; Theoretical
Non-volatile Matter Content	77 ± 2; Theoretical
Film Thickness/Coat	Wet: 250 - 500 Micrometers Dry: 152 - 305 Micrometers
Drying Times	Depends on temperature, humidity, air movements and film thickness
Touch Dry Recoat	2 - 3 Hours 6 - 8 Hours
Theoretical Coverage	A guide to the theoretical coverage which can be achieved under normal conditions is 2 - 4 m ² /liter /coat.
Application	Special Spray Gun
Thinner	Water
Dilution	Maximum 10% (If Required)
Cleaning Up	Clean all equipment with clean water immediately after use.

Surface Preparation

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down the abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of paris or white cement. Allow to dry. Use recommended application procedure for application. Stir thoroughly before use.

Recommended Paint System

Brighto Acrylic Primer	1 Coat
Brighto Texo Compound	1 Coat
Brighto Acrylic Rock Top Coat / All Weather Matt / Silk	1 - 2 Coats

Safety, Health and Environmental Information

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.