





gaf.com



Accessory

Description

EverGuard Extreme® TPO 45
Mil Utility Flashing Membrane
provides roofing contractors with
an easy-to-install factory-built
detail. EverGuard Extreme® TPO
45 Mil Utility Flashing Membrane
is constructed using GAF's proven,
durable, high-performance
EverGuard Extreme® TPO.
This accessory is used to strip-in
coated metal flanges and at
areas that require a reinforced
membrane for flashing.

- Cost effective...
 Reliability is built in; made
 with GAF EverGuard Extreme®
 TPO membrane
- Improved reliability...
 Factory-built accessories reduce risk of leaks and callbacks

Application

EverGuard Extreme® TPO 45
Mil Utility Flashing Membrane
is designed for use with GAF
EverGuard Extreme® TPO,
EverGuard® TPO, and EverGuard®
Freedom™ Self-Adhering TPO.
45 Mil Utility Flashing Membrane
may be installed on:

- EverGuard® TPO 45, 60, and 80 mil mechanically attached or fully adhered roofing systems
- EverGuard Extreme® TPO 50, 60, 70, and 80 mil mechanically attached or fully adhered roofing systems
- EverGuard® Freedom™ TPO 45, 60, and 80 mil self-adhering roofing systems

See published application and specifications manual for detailed instructions.

Product Information

EverGuard Extreme® TPO 45 Mil Utility Flashing Membrane comes standard in White. The membrane is EverGuard Extreme® TPO 45 mil reinforced, so it's durable and versatile.



45 Mil Utility Flashing Membrane

- Manufactured to strict specifications using GAF's high-performance EverGuard Extreme® TPO formulation
- Designed for ease of installation
- Used in a variety of flashing details, including stripping-in coated metal

SPECIFICATIONS	
Roll Size:	8" x 100' (203 mm x 30.5 m) rolls
Material:	45 mil reinforced TPO membrane
SHIPPING SPECIFICATIONS	
Weight per roll:	18 lbs (8.2 kg)

Visit gaf.com to see our full line of prefabricated accessories!