

Injection Port | Inlet Liner ConnecTite

Spot the Difference in the SGE Lineup!

The SGE inlet liner range aims to make it simple for all gas chromatographers to select the correct liner.

Choosing the right inlet liner and injection parameters can increase peak areas and reduce detection limits by up to 300 %.

- Easy to choose color coded by geometry to simplify your selection.
- Easy to use contains o-rings so you're ready to go.
- Confidence in your analysis certified deactivation.

Features and benefits

- Robust and durable for longer life, less maintenance downtime and reduced maintenance costs.
- ConnecTite liners facilitate maximum transfer of sample to the GC column and inhibit sample degradation by reducing contact with hot metal components inside the inlet.
- A hole in the liner body maintains gas flows in systems equipped with electronic pressure control.
- ConnecTite liners with a hole near the bottom are ideal for analyses where early eluting compounds may be affected by a tailing solvent peak.
- ConnecTite liners with a hole at the top improve analyses of aqueous samples.
- ConnecTite liners with a hole at the top are also ideal for analyses where compounds of interest elute away from the solvent peak.



Color coded orange

Recommended applications

ConnecTite liners are recommended for the following sample or injection modes:

- Trace level analysis.
- · Direct injection.
- Active compounds.
- Aqueous samples.

Product specifications

ConnecTite available for Agilent, PerkinElmer, Shimadzu 2010, Thermo Scientific, and Bruker/Varian 1075/1077 injectors.

Injection Port | Inlet Liner ConnecTite continued

Injector	Length (mm)	OD (mm)	ID (mm)
Agilent	78.5	6.3	4
Bruker/Varian	54	4.6	0.5
Bruker/Varian	54	4.6	0.8
Bruker/Varian	72	6.3	4
PerkinElmer	92	6.2	4
Shimadzu	95	5	2.6
Shimadzu	95	5	3.4
Thermo	105	8	5
Thermo	78.5	6.3	4

For more information about this product visit www.trajanscimed.com or contact techsupport@trajanscimed.com $\,$